



Product End-of-Life Disassembly Instructions

Product Category: Networking Equipment

Marketing Name / Model

[List multiple models if applicable.]

HP A5920AF-24XG (JG296A)

Purpose: The document is intended for use by end-of-life recyclers or treatment facilities. It provides the basic instructions for the disassembly of HP products to remove components and materials requiring selective treatment, as defined by EU directive 2002/96/EC, Waste Electrical and Electronic Equipment (WEEE).

1.0 Items Requiring Selective Treatment

1.1 Items listed below are classified as requiring selective treatment.

1.2 Enter the quantity of items contained within the product which require selective treatment in the right column, as applicable.

Item Description	Notes	Quantity of items included in product
Printed Circuit Boards (PCB) or Printed Circuit Assemblies (PCA)	With a surface greater than 10 sq cm	3
Batteries	All types including standard alkaline and lithium coin or button style batteries	2
Mercury-containing components	For example, mercury in lamps, display backlights, scanner lamps, switches, batteries	0
Liquid Crystal Displays (LCD) with a surface greater than 100 sq cm	Includes background illuminated displays with gas discharge lamps	0
Cathode Ray Tubes (CRT)		0
Capacitors / condensers (Containing PCB/PCT)		0
Electrolytic Capacitors / Condensers measuring greater than 2.5 cm in diameter or height		0
External electrical cables and cords		0
Gas Discharge Lamps		0
Plastics containing Brominated Flame Retardants weighing > 25 grams (not including PCBs or PCAs already listed as a separate item above)		6
Components and parts containing toner and ink, including liquids, semi-liquids (gel/paste) and toner	Include the cartridges, print heads, tubes, vent chambers, and service stations.	0
Components and waste containing asbestos		0
Components, parts and materials containing refractory ceramic fibers		0
Components, parts and materials containing radioactive substances		0

2.0 Tools Required

List the type and size of the tools that would typically be used to disassemble the product to a point where components and materials requiring selective treatment can be removed.

EL-MF877-00

Template Revision B

Page 1

Tool Description	Tool Size (if applicable)
Screw driver	2#

3.0 Product Disassembly Process

3.1 List the basic steps that should typically be followed to remove components and materials requiring selective treatment:

1. Unscrew the Power Cable Holder 1.
2. Unscrew the screws on mounting angle 2, and then remove mounting angle 2.
3. Unscrew the screws on mounting angle 3, and then remove mounting angle 3.
4. Unscrew all screws of battery 4, and then remove battery 4 from the chassis.
5. Unscrew all screws on blank panel 5, and then remove panel 5 from chassis.
6. Unscrew all screws on fan 6, and then remove fan 6 from the chassis.
7. Unscrew all screws, and then remove the top cover 7.
8. Remove all of the inner cables.
9. Unscrew all screws on PCB 8, and then remove PCB 8 from the chassis.
10. Remove part 9 from PCB 8.
11. Remove all of the labels from the chassis.
12. Unscrew all screws 5-2 , and then remove handle 5-1 from blank panel 5-4.
13. Remove the part 5-3.
14. Unscrew all screws, and then remove fan 6-9 from fan rack 6-1..
15. Unscrew all screws, and then remove part 6-8 from fan rack 6-1.
16. Unscrew all screws, and then remove pcb 6-7 from fan rack 6-1.
17. Unscrew all screws, and then remove part 6-6 from fan rack 6-1.
18. Unscrew all screws, and then remove part 6-5 from fan rack 6-1.
19. Unscrew all screws, and then remove part 6-4 from fan rack 6-1.
20. Unscrew all screws, and then remove part 6-3 from fan rack 6-1.
21. Unscrew all screws, and then remove handle 6-2 from fan rack 6-1.

3.2 Optional Graphic. If the disassembly process is complex, insert a graphic illustration below to identify the items contained in the product that require selective treatment (with descriptions and arrows identifying locations).




Figure 1 Remove mounting angle




Figure 2 Rear of HP S5830-24S




Figure 3 Treatments to the top cover




Figure 4 Treatments to pcb 8




Figure 5 Treatments to blank panel 5




Figure 6 Treatments to front panel 6