

Overview

Aruba 501 Wireless Client Bridge Series

The Aruba 501 Wireless Client Bridge enables you to easily integrate devices with no native wireless support into a wireless LAN (WLAN). It provides strong enterprise-class layered security features, including an IEEE 802.1X supplicant, to protect the network from intrusions.

The 501 Wireless Client Bridge can bridge up to 15 Ethernet client devices running a legacy networking protocol to the WLAN – extending wireless network access to a wide range of protocols. An integrated serial to TCP/IP converter enables a RS-232 asynchronous terminal device to communicate with a compatible station on the network. Hardware-accelerated encryption provides higher performance when using WPA2/AES security.

This bridge provides the benefits of wireless mobility for devices like electronic cash registers, scales, servers, printers, medical equipment and other devices. It can be deployed in any location where a WLAN signal is available – saving the time and expense of installing Ethernet cables for wired network access.

The 501 Wireless Client Bridge integrates into the Aruba Mobile First solution architecture and is interoperable with the IEEE 802.11a/b/g/n/ac wireless network infrastructure in a multi-vendor environment.



Aruba 501 Wireless Client Bridge Series

Models

Aruba 501 Wireless Client Bridge

J9835A

Highlights

- Link up to 15 Ethernet devices or an RS232 serial device to a wireless network at Gigabit speeds
- One dual-band three spatial-stream MIMO radio running up to 1.3 Gbps
- Support for IEEE 802.11b/g/n and 802.11a/n/ac WLAN networks
- Fast roaming between access points
- Web-based configuration

Standard Features

Quality of Service (QoS)

- **Network management**
 - Support for DSCP and WMM
 - SNMP v2c, SNMP v3, MIB-II with traps, and RADIUS authentication client MIB (RFC 2618)
 - Embedded HTML management tool with secure access
 - Scheduled configuration and firmware upgrades via a network management station
 - **Diagnostic**
 - RSSI logging
 - Email alert tool
-

Connectivity

- **IEEE 802.3af PoE support**
 - Simplifies deployment and dramatically reduces installation costs by helping eliminate the time and cost involved in supplying local power at each client bridge
 - **Auto-MDIX**
 - Provides automatic adjustments for straight-through or crossover cables on all 10/100/1000 ports
 - **IEEE 802.11h with International-Telecommunication-Union (ITU) compliance**
 - Selects the channel automatically, based on the access point it connects to; and avoids DFS (Dynamic-Frequency-Selection) issues by following the access point to a clear channel
-

Mobility

- **Anywhere, anytime wireless coverage**
 - Provides single IEEE 802.11a/b/g/n/ac radio client bridge
 - Offers radio software-selectable configuration of frequency bands
 - Utilizes IEEE 802.3af PoE or local power supply
 - **Interoperability**
 - Meets Wi-Fi Alliance Certification standards, including IEEE 802.11a/b/g/n/ac and WPA2—to ensure multivendor interoperability
 - **Supported devices**
 - Support Windows-based PCs equipped with Ethernet cards; includes point-of-sale devices, scales, network printers, thin clients Mac/Apple machines, Linux/Unix workstations, Ethernet-enabled appliances, medical equipment, or manufacturing machinery
 - Connects RS232 asynchronous terminal devices to the wireless network
 - **Multiple devices**
 - Connects up to 15 Ethernet-enabled devices via a multiport switch
-

Security

- **IEEE 802.1X support**
 - Provides user authentication with support for EAP-TLS and PEAP—with choice of Advanced Encryption Standard (AES), Temporal Key Integrity Protocol (TKIP), and Wired Equivalent Privacy (WEP) encryption for protecting wireless traffic between authenticated clients and the access point
 - **Choice of IEEE WPA2, WPA or WEP**
 - Secures the data integrity of wireless traffic, using robust AES or TKIP encryption
-

Warranty and support

- **Limited Lifetime Warranty**
 - **Software releases**
 - To find software for your product, visit Aruba Support
-



Configuration Information

Build To Order: BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

BTO Models

Remarks	Description	SKU
	Aruba 501 Wireless Client Bridge <ul style="list-style-type: none"> 1 RJ-45 autosensing 10/100/1000 port 	J9835A
Notes:	OCA Only Model Selection Form - HPE Offering > Aruba > Client Bridge: Aruba 501 Wireless Client Bridge	

Antennas

Dual-Band Antennas

Std (Min 0 // max 1) User Selection (min 0 // max 1)

1	AP-ANT-20W 2.4-2.5GHz (2dBi)/4.9-5.875GHz (2dBi) Compact Omni-Dir DMt Indr White Antenna	JW011A
1	AP-ANT-1W 2.4-2.5GHz (4dBi)/4.9-5.875GHz (6dBi) Hi Gain Dual-band Omni-Dir Indoor Antenna	JW009A
1	AP-ANT-19 2.4/5G Dual Band Omni-Dir 3dBi/6dBi Indr/Otrd RPSMA Cnctr Ant w/36in Intgrtd Cable	JW004A

Configuration Rules

1 Must select Qty 0 or Qty 3

- Notes:**
- AP-ANT-1W, and AP-ANT-20W are usually direct connect to the chassis
 - AP-ANT-19 includes external antenna mounting brackets

Power Options

Remarks	Description	SKU
	Power Options	
*	Aruba 501 Client Bridge 5V Power Supply	J9405C
**	AP-POE-AFGE 1-Port GbE 802.3af 15.4W midspan injector	R6P68A
Notes:	<ul style="list-style-type: none"> - *Localization required. (See Localization Menu) - **If this Power Supply is selected, bring in (Min 1 // Max 1) Localized power cord based on the Aruba Localization Menu 	



Technical Specifications

Aruba 501 Wireless Client Bridge (J9835A)		
I/O ports and slots	1 RJ-45 autosensing 10/100/1000 port; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 1 RS-232C serial console port	
Characteristics	Radios (built-in)	802.11 a/b/g/n/ac
	Radio operation modes	Client bridge
	Wi-Fi Alliance Certification	a/b/g/n/ac Wi-Fi Certified
	Antenna connector	Three RP-SMA
	Antenna	2 dBi dual-band omnidirectional
	Number of external antennas	3
	Three spatial streams for up to 1.3 Gbps PHY rate	
	Three RP-SMA connectors for a range of antenna options	
Notes: When using outdoor antennas, customer must supply RP-SMA to Type N adapter		
Physical characteristics	Dimensions	5.5 (w) x 1.3 (d) x 5.0 (h) in (13.97 x 3.3 x 12.7 cm)
	Weight	2.01 lb (0.91 kg)
Environment	Operating temperature	32°F to 122°F (0°C to 50°C)
	Operating relative humidity	5% to 95%, non-condensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Non-operating/Storage relative humidity	5% to 95%, non-condensing
	Shock and vibration	EN 61373
Electrical characteristics	Altitude	10,000 feet (3,048 meters)
	Description	IEEE 802.3af PoE compliant or 5-15 VDC from external DC power source
	Maximum power rating	9 W from external DC power source 11 W from PoE power source

RF Performance Table

	Maximum transmit power (dBm) per transmit chain and includes the 2dBi dipole antenna that ships with the bridge	Receiver sensitivity (dBm) per receive chain and includes the 2dBi dipole antenna that ships with the bridge
802.11b 2.4 GHz		
1 Mbps	21	-96
11 Mbps	21	-88
802.11g 2.4 GHz and 802.11a 5 GHz		
6 Mbps	20 (21 at 2.4 GHz)	-92 (-93 at 2.4 GHz)
54 Mbps	19	-75
802.11n HT20 2.4 GHz and 5 GHz		
MCS0/8/16	18 (21 at 2.4 GHz)	-90 (-93 at 2.4 GHz)
MCS7/15/23	15 (16 at 2.4 GHz)	-71
802.11n HT40 2.4 GHz and 5 GHz		
MCS0/8/16	20 (14 at 2.4 GHz)	-90
MCS7/15/23	15 (14 at 2.4 GHz)	-68
802.11ac VHT80 5 GHz		
MCS0	20	-86
MCS9	13	-59
Maximum capability of the hardware provided. Maximum transmit power is limited by local regulatory settings.		

Technical Specifications

Wireless Radio Specifications

- Indoor, single radio, 5 GHz 802.11ac / 2.4 GHz 802.11n
- Software automatically searches for AP on 5 GHz and 2.4 GHz
- 3x3 MIMO with three spatial streams and up to 1.3 Gbps
- wireless data rate
- Supported frequency bands (country-specific restrictions apply):
 - --2.4000 GHz to 2.4835 GHz
 - --5.150 GHz to 5.250 GHz
 - --5.250 GHz to 5.350 GHz
 - --5.470 GHz to 5.725 GHz
 - --5.725 GHz to 5.850 GHz
- Available channels: Dependent upon configured regulatory domain
- Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
- Maximum transmit power varies by country
- Supported radio technologies:
 - 802.11b: Direct-sequence spread-spectrum (DSSS)
 - 802.11a/g/n/ac: Orthogonal frequency-division multiplexing (OFDM)
 - 802.11n/ac: 3x3 MIMO with up to three spatial streams
- Supported modulation types:
 - 802.11b: BPSK, QPSK, CCK
 - 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM
 - 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
- Transmit power data is per chain and includes the dipole antenna that ships with the Aruba 501 Wireless Client Bridge. The receiver sensitivity also includes the dipole antenna gain.
- Maximum ratio combining (MRC) for improved receiver performance
- Cyclic delay diversity (CDD) for improved downlink RF performance
- Short guard interval for 20-MHz, 40-MHz and 80-MHz channels
- Space-time block coding (STBC) for increased range and improved reception
- Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
- Supported data rates (Mbps):
 - 802.11b: 1, 2, 5.5, 11
 - 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54
 - 802.11n: 6.5 to 450 (MCS0 to MCS23)
 - 802.11ac: 6.5 to 1,300 (MCS0 to MCS9, NSS = 1 to 3)
- 802.11n high-throughput (HT) support: HT 20/40
- 802.11ac very high throughput (VHT) support: VHT 20/40/80
- 802.11n/ac packet aggregation: A-MPDU, A-MSDU

Regulatory

- **I/O ports and slots**
FCC Part 15.247; EN 300 328; FCC Part 15.407; MIC Notice No. 88, App. 43 & 45; EN 301 893; RSS-210
 - **Safety**
UL 2043; UL 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1
 - **RF Exposure**
FCC Bulletin OET-65C; RSS-102; EN 62311
 - **Emissions**
EN 55022 Class B; EN 60601-1-2; EN 301 489-1; EN 301 489-17; ICES-003 Class B; FCC Part 15, VCCI Class B
 - **Regulatory model numbers**
MRLBB-1302
-



Technical Specifications

Security

- **IEEE 802.1X support**
Provides user authentication with support for EAP-TLS and PEAP—with choice of Advanced Encryption Standard (AES), Temporal Key Integrity Protocol (TKIP), and Wired Equivalent Privacy (WEP) encryption for protecting wireless traffic between authenticated clients and the access point
 - **Choice of IEEE, WPA2, WPA, or WEP**
Secures the data integrity of wireless traffic, using robust AES or TKIP encryption
-

Warranty and Support

- Limited Lifetime Warranty
-

Software Releases

- To find software for your product, visit [Aruba Support](#)
-





Summary of Changes

Date	Version History	Action	Description of Change:
01-Aug-2022	Version 11	Changed	Configuration Information section was updated.
08-Sep-2020	Version 10	Changed	Configuration Information section was updated. New SKUs were added.
06-Jan-2020	Version 9	Changed	Configuration Information section was updated.
04-Sep-2018	Version 8	Changed	Configuration section added with the updated information
10-Mar-2017	Version 7	Changed	Document name and content updated with Aruba information
01-Aug-2016	Version 6	Changed	Adding #AC3 Option on Configuration Menu
10-Jun-2016	Version 5	Changed	Changes made on Technical Specifications
01-Dec-2015	Version 4	Changed	Overview and Technical Specifications updated
01-Dec-2014	Version 3	Changed	Warranty and support updated
20-Dec-2013	Version 2	Added	Configuration was added.
09-Dec-2013	Version 1	New	New QuickSpecs



Copyright

Make the right purchase decision.
Contact our presales specialists.



© Copyright 2022 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

HPE access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.
UNIX® is a registered trademark of The Open Group.

To learn more, visit: <http://www.hpe.com/networking>

c04111338 - 14754 - Worldwide - V11 - 01-August-2022