

MODELS

Compaq P710 CRT Monitor
210189-xxx

Note: AssetControl monitor. AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability.

SPECIFICATIONS

Compaq P710 CRT Monitor

Type	Color auto- scanning with Digital Control			
Picture Tube (diagonal)	17 in/43 Diamondtron NF CRT			
Viewable (diagonal)	16 in/41 cm			
Pitch	0.25 mm Aperture Grill Pitch			
Graphic Preset Modes	1600 x 1200	1280 x 1024	1024 x 768	800 x 600
Note: All modes are non-interlaced unless specified otherwise. V Frequency shown Maximum/Presets.	76 Hz/75 Hz,	85 Hz/75 Hz,	115 Hz/75 Hz,	130 Hz/75 Hz,
		85 Hz	85 Hz	85 Hz
	640 x 480			
	130 Hz/60 Hz,			
	85 Hz			
Text Mode	720 x 400			
	70 Hz			
Mac Compatible Modes	1152 x 870			
Note: Adapter required.	75 Hz			
User-Programmable Modes	11 (5 Preset Modes and 6 Pre-loads)			
Anti-Glare/Anti-Reflection/Anti-Static	Yes/Yes/Yes			
Plug and Play	Yes			
Plug and Play Protocol	DDC1/2B			
Dual Video Inputs	No			
Approvals/Certifications				
MPR-II (Low Emissions)	Yes			
TCO-99	Yes			
Energy Star Compliant	Yes			
UL Listing	Yes			
ISO9241-3 VOT Guidelines Approval	Yes			
FCC Approval	Yes			
CE Marketing (including PFC)	Yes (European assemblies only)			
GS Marketing	Yes			
Analog Controls	No			
Brightness, Contrast	Yes			
On-Screen Controls	Yes			
Language Selection				
English	Yes			
Spanish	Yes			
French	Yes			
German	Yes			
Dutch	No			
Italian	No			
Japanese	Yes			

SPECIFICATIONS *(continued)*

Compaq P710 CRT Monitor *(continued)*

Note: AssetControl monitor. AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability.

User Controls

Sizing and Positioning	Yes
Pincushion	Yes
Pincushion Balance	Yes
Trapezoid	Yes
Tilt (rotation)	Yes
Color temperature	Yes
Degauss	Yes
Parallelogram	Yes
Individual color control	No
Zoom	No
Moiré Cancellation	Yes
Convergence	No
Factory Reset	Yes
Corner Purity Adjustment	No

AssetControl Yes

Note: When used with Compaq Intelligent Manageability CPUs and appropriate network software.

Pixel Clock Frequency (Maximum)	208 MHz (1600x1200, 76 Hz, 95 kHz)
Input Impedance	75 ohms
Horizontal Frequency	30 to 96 kHz
Vertical Frequency	50 to 130 Hz
Power Supply	90 to 260 VAC (200 to 260 VAC for Europe)
Maximum Power Rating	95 W
USB Capabilities	No
Synchronized Input	Separate H, V synchronized
Signal Cable	Detachable 15-in D-sub to 15-pin D-sub cable. D-sub connector on monitor
Maximum Phosphorus Size	12.8 x 9.6 in/325.1 x 243.8 mm (16 in/406.4 mm diagonal)
Dimensions (HxWxD)	16.2 x 16.1 x 17.1 in/412.6 x 410.2 x 435.3 mm
Weight	38.6 lbs/17.5 kg
Temperature	
Operating	50° to 95°F/10° to 35°C
Non-operating	-4° to 140°F/-20° to 60°C
Humidity	
Operating	20% to 80%
Non-operating	10% to 90%
Warranty	Three-year parts, three-year on-site labor, or next business day direct replacement

Note: Certain restrictions apply. Consult the Compaq Customer Service Support Center for details.

COMPATIBILITY

Graphics Controllers

3Dlabs Oxygen GVX1
ATI RAGE PRO
ATI Mobility P
ATI RAGE PRO TURBO 2X
Diamond Viper V730
Diamond Viper V770 Ultra
ELSA GLoria II
ELSA Synergy II
Matrox Millennium II
Matrox Millennium G100 (AGP)
Matrox Millennium G200 (PCI)
Matrox Millennium G400
Matrox Millennium G450 (AGP and PCI)
NVIDIA GeForce 2 GTS
NVIDIA GeForce 256
NVIDIA TNT2 M64
NVIDIA TNT2 Pro
NVIDIA Vanta
RAGE ATI IIC
S3 VIRGE/MX (AGP)
Velocity 4000

Chipsets

Intel 810
Intel 810e
Intel 815