

Overview

Models

HP X132 10G SFP+ LC SR Transceiver	J9150A
HP X132 10G SFP+ LC LR Transceiver	J9151A
HP X132 10G SFP+ LC LRM Transceiver	J9152A
HP X132 10G SFP+ LC ER Transceiver	J9153A

Technical Specifications

HP X132 10G SFP+ LC SR Transceiver (J9150A)

A 10-Gigabit transceiver in SFP+ form-factor that supports the 10-Gigabit SR standard, providing 10-Gigabit connectivity up to 300 m on multimode fiber.

Ports	1 LC 10-GbE port (IEEE 802.3ae Type 10Gbase-SR); Duplex: full only
Connectivity	Connector type LC
Physical characteristics	Wavelength 850 nm
	Dimensions 2.19(d) x 0.54(w) x 0.47(h) in. (5.57 x 1.38 x 1.19 cm)
	Weight 0.04 lb. (0.02 kg)
	Transceiver form factor SFP+
Environment	Operating temperature 32°F to 158°F (0°C to 70°C)
	Operating relative humidity 0% to 85%, noncondensing
	Nonoperating/Storage temperature -40°F to 185°F (-40°C to 85°C)
	Altitude up to 10,000 ft. (3 km)
Electrical characteristics	Power consumption typical 0.6 W
	Power consumption maximum 0.8 W
Cabling	Cable type: 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Maximum distance: <ul style="list-style-type: none">• 2-26m with 62.5 µm multimode cable @ 160 MHz*km• 2-33m with 62.5 µm multimode cable @ 200 MHz*km• 2-66m with 50 µm multimode cable @ 400 MHz*km• 2-82m with 50 µm multimode cable @ 500 MHz*km• 2-300m with 50 µm multimode cable @ 2000 MHz*km
	Cable length 2-300m
	Fiber type Multi Mode
Notes	For fiber patch cords, use Ultra Physical Contact (UPC) surface termination/polish. Angled Physical Contact (APC) is not recommended.
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Technical Specifications

HP X132 10G SFP+ LC LR Transceiver (J9151A)

A 10-Gigabit transceiver in SFP+ form-factor that supports the 10-Gigabit LR standard, providing 10-Gigabit connectivity up to 10 km on single-mode fiber.

Ports	1 LC 10-GbE port (IEEE 802.3ae Type 10Gbase-LR); Duplex: full only
Connectivity	Connector type LC
Physical characteristics	Wavelength 1310 nm
	Dimensions 2.19(d) x 0.54(w) x 0.47(h) in. (5.57 x 1.38 x 1.19 cm)
	Weight 0.04 lb. (.02 kg)
	Transceiver form factor SFP+
Environment	Operating temperature 32°F to 158°F (0°C to 70°C)
	Operating relative humidity 0% to 85%, noncondensing
	Nonoperating/Storage temperature -40°F to 185°F (-40°C to 85°C)
Electrical characteristics	Altitude up to 10,000 ft. (3 km)
	Power consumption typical 0.9 W
	Power consumption maximum 1 W
Cabling	Cable type: Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1; Maximum distance: <ul style="list-style-type: none">• 2m-10km with 9/125 µm single-mode cable
	Cable length 2m to 10km
	Fiber type Single Mode
Notes	Conditioning patch cord cables are not supported. For fiber patch cords, use Ultra Physical Contact (UPC) surface termination/polish. Angled Physical Contact (APC) is not recommended.
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Technical Specifications

HP X132 10G SFP+ LC LRM Transceiver (J9152A)	Ports	1 LC 10-GbE port (IEEE 802.3aq Type 10Gbase-LRM); Duplex: full only
	Connectivity	Connector type LC
A 10-Gigabit transceiver in SFP+ form-factor that supports the 10-Gigabit LRM standard, for 10-Gigabit connectivity up to 220 m on legacy multimode fiber.	Physical characteristics	Wavelength 1310 nm
		Dimensions 2.19(d) x 0.54(w) x 0.47(h) in. (5.57 x 1.38 x 1.19 cm)
		Weight 0.04 lb. (.02 kg)
		Transceiver form factor SFP+
	Environment	Operating temperature 32°F to 158°F (0°C to 70°C)
		Operating relative humidity 0% to 85%, noncondensing
		Nonoperating/Storage temperature -40°F to 185°F (-40°C to 85°C)
		Altitude up to 10,000 ft. (3 km)
	Electrical characteristics	Power consumption typical 0.7 W
		Power consumption maximum 1 W
	Cabling	Cable type: 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively (a mode conditioning patch cord may be needed in some multimode fiber installations); Maximum distance: <ul style="list-style-type: none">● 0.5-220m with 62.5 µm multimode cable @ 160/500 MHz*km● 0.5-220m with 62.5 µm multimode cable @ 200/500 MHz*km● 0.5-100m with 50 µm multimode cable @ 400/400 MHz*km● 0.5-220m with 50 µm multimode cable @ 500/500 MHz*km● 0.5-220m with 50 µm multimode cable @ 1500/500 MHz*km
		Cable length 0.5m to 220m
		Fiber type Multi Mode
	Notes	For OM3 cable (50 µm multimode @ 1500/500 MHz*km), a mode-conditioning patch cord is not required. Other multimode cables may require mode-conditioning patch cords to achieve the maximum distances listed above. For fiber patch cords, use Ultra Physical Contact (UPC) surface termination/polish. Angled Physical Contact (APC) is not recommended.
	Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Technical Specifications

HP X132 10G SFP+ LC ER Transceiver (J9153A)

The SFP+ ER Transceiver will transmit 10Gbps over up to 40km using standard OM3 fiber cable. This product expands the HP Networking transceiver portfolio for connections from 0m to 40km. Use only genuine HP transceivers with your HP Networking equipment to ensure reliability and support.

Ports	1 LC 10-GbE port (IEEE 802.3ae Type 10Gbase-ER); Duplex: full only
Connectivity	Connector type LC
Physical characteristics	Wavelength 1550 nm
	Dimensions 2.22(d) x 0.55(w) x 0.47(h) in. (5.65 x 1.39 x 1.19 cm)
Environment	Weight .04 lb., Fully loaded
	Transceiver form factor SFP+
	Operating temperature 32°F to 158°F (0°C to 70°C)
	Operating relative humidity 5% to 95%, noncondensing
	Nonoperating/Storage temperature -40°F to 185°F (-40°C to 85°C)
Electrical characteristics	Nonoperating/Storage relative humidity 5% to 95%, noncondensing
	Altitude up to 10,000 ft. (3 km)
	Power consumption typical 1.3 W
Cabling	Power consumption maximum 1.5 W
	Cable type: Single-mode fiber optic, complying with ITU-T G.652; Maximum distance: <ul style="list-style-type: none">• 40km
Notes	Fiber type Single Mode
	Check switch release notes for minimum version of software required to support this transceiver. Some switches have limits as to how many of this particular transceiver can be installed. See the release notes of the switch software/firmware being used for more details.
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

To learn more, visit: www.hp.com/networking

© Copyright 2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.