

HPE MSR2000 Router Series



Key features

- 4 Mpps forwarding; converged high-performance routing, switching, security, voice, mobility
- Embedded security features with hardware-based encryption, firewall, NAT, and VPNs
- Integrated 1/10GbE WAN and LAN, fiber (SFP)
- No additional licensing complexity; no cost for advanced features
- Zero-touch solution, with single-pane-of-glass management
- The new 2003X router supports 10GbE ports with Comware v9 OS

Product overview

HPE MSR2000 Router Series, the next generation of router from HPE, is a component of the HPE FlexNetwork solution. These routers feature a modular design that delivers unmatched application services for small- to medium-sized branch offices. This gives your IT personnel the benefit of reduced complexity and simplified configuration, deployment, and management.

The HPE MSR2000 Router Series provides an agile, flexible network infrastructure that enables you to quickly adapt to your changing business requirements while delivering integrated concurrent services on a single, easy-to-manage platform.

Features and benefits

Performance

- Excellent forwarding performance
Provides forwarding performance up to 4 Mpps meets the bandwidth-intensive application demands of enterprise businesses
- Powerful security capacity
Includes an embedded hardware encryption accelerator to improve encryption performance; encryption throughput can be up to 3 Gbps with a maximum of 1000 IPsec VPN tunnels

Product architecture

- Ideal multiservice platform
Provides WAN router, Ethernet switch, wireless LAN, 3G/4G WAN, firewall, VPN, and SIP/voice gateway, all in one device
- Advanced hardware architecture
Supports multicore processors, gigabit switching, and PCIe bus
- New operation system version
Ships with new Comware v7 operating system delivering the latest in [virtualization](#) and routing

Connectivity

- High-density port connectivity
Provides up to three interface module slots and up to 15 Fast Ethernet ports
- Multiple WAN interfaces
Provides a traditional link with E1, T1, Serial, and ISDN links; high-density Ethernet access with WAN Gigabit Ethernet and LAN 4- and 9-port Fast Ethernet; and mobility access with 3G SIC module and 3G/4G USB modems
- Packet storm protection
Protects against broadcast, multicast, or unicast storms with user-defined thresholds
- Loopback
Supports internal loopback testing for maintenance purposes and an increase in availability. Loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- 3G/4G LTE access support
Provides 3G wireless access for primary or backup connectivity via a 3G SIC module certified on various cellular networks. Optional carrier 3G/4G LTE USB modems are available
- USB interface
Uses USB memory disk to download and upload configuration and OS image files; supports an external USB 3G/4G modem for a 3G/4G WAN uplink
- Flexible port selection
Provides a combination of fiber and copper interface modules, 100/1000BASE-X support, and 10/100/1000BASE-T auto-speed detection plus auto duplex and MDI/MDIX

Layer 2 switching

- Spanning Tree Protocol (STP)
Supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping
Controls and manages the flooding of multicast packets in a Layer 2 network
- Port mirroring
Duplicates port traffic (ingress and egress) to a local or remote monitoring port
- VLANs
Supports IEEE 802.1Q-based VLANs
- sFlow®
Allows traffic sampling
- Define port as switched or routed
Supports command switch to easily change switched ports to routed (maximum four Fast Ethernet ports)



Layer 3 routing

- Static IPv4 routing
Provides simple manually configured IPv4 routing
- Routing Information Protocol (RIP)
Uses a distance vector algorithm with UDP packets for route determination; supports RIPv1 and RIPv2 routing; includes loop protection
- Open shortest path first (OSPF)
Delivers faster convergence; uses this link-state routing Interior Gateway Protocol (IGP), which supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- Border Gateway Protocol 4 (BGP-4)
Delivers an implementation of the Exterior Gateway Protocol (EGP) utilizing path vectors; uses TCP for enhanced reliability for the route discovery process; reduces bandwidth consumption by advertising only incremental updates; supports extensive policies for increased flexibility; scales to extremely large networks
- Intermediate system to intermediate system (IS-IS)
Uses a path vector Interior Gateway Protocol (IGP), which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)
- Static IPv6 routing
Provides simple manually configured IPv6 routing
- Dual IP stack
Maintains separate stacks for IPv4 and IPv6 to ease the transition from an IPv4-only network to an IPv6-only network design
- Routing Information Protocol next generation (RIPng)
Extends RIPv2 to support IPv6 addressing
- OSPFv3
Provides OSPF support for IPv6
- BGP+
Extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- IS-IS for IPv6
Extends IS-IS to support IPv6 addressing
- IPv6 tunneling
Allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet; supports manually configured, 6 to 4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels; is an important element for the transition from IPv4 to IPv6
- Multiprotocol Label Switching (MPLS)
Uses BGP to advertise routes across Label Switched Paths (LSPs) but uses simple labels to forward packets from any Layer 2 or Layer 3 protocol, which reduces complexity and increases performance; supports graceful restart for reduced failure impact; supports LSP tunneling and multilevel stacks
- Multiprotocol Label Switching (MPLS) Layer 3 VPN
Allows Layer 3 VPNs across a provider network; uses Multiprotocol BGP (MP-BGP) to establish private routes for increased security; supports RFC 2547bis multiple autonomous system VPNs for added flexibility; supports IPv6 MPLS VPN
- Multiprotocol Label Switching (MPLS) Layer 2 VPN
Establishes simple Layer 2 point-to-point VPNs across a provider network using only MPLS Label Distribution Protocol (LDP); requires no routing and therefore decreases complexity, increases performance, and allows VPNs of non-routable protocols; uses no routing information for increased security; supports Circuit Cross Connect (CCC), Static Virtual Circuits (SVCs), Draft Martini, and Draft Kompella technologies
- Routing policy
Allows custom filters for increased performance and security; supports ACLs, IP prefix, AS paths, community lists, and aggregate policies



Layer 3 services

- Address Resolution Protocol (ARP)
Determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- User Datagram Protocol (UDP) helper
Redirects UDP broadcasts to specific IP subnets to prevent server spoofing
- Dynamic Host Configuration Protocol (DHCP)
Simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets

Quality of service (QoS)

- Nested QoS
Provides a built-in QoS engine that supports nested QoS (same to hierarchical QoS) and can implement a hierarchical scheduling mechanism based on ports, user groups, users, and user services
- Traffic policing
Supports Committed Access Rate (CAR) and line rate
- Congestion management
Supports FIFO, PQ, CQ, WFQ, CBQ, and RTPQ
- Weighted random early detection (WRED)/random early detection (RED)
Delivers congestion avoidance capabilities through the use of queue management algorithms
- Other QoS technologies
Supports traffic shaping, MPLS QoS, and MP QoS/LFI

Security

- Dynamic Virtual Private Network (DVPN)
Collects, maintains, and distributes dynamic public addresses through the VPN Address Management (VAM) protocol, making VPN establishment available between enterprise branches that use dynamic addresses to access the public network. Compared to traditional VPN technologies, DVPN technology is more flexible and has richer features, such as NAT traversal of DVPN packets, AAA identity authentication, IPSec protection of data packets, and multiple VPN domains
- IPSec VPN
Supports DES, 3DES, and AES 128/192/256 encryption, and MD5 and SHA-1 authentication
- Access control list (ACL)
Supports powerful ACLs for both IPv4 and IPv6. ACLs are used for filtering traffic to prevent unauthorized users from accessing the network, or for controlling network traffic to save resources. Rules can either deny or permit traffic to be forwarded, be based on a Layer 2 header or a Layer 3 protocol header, be set to operate on specific dates or times
- Terminal Access Controller Access-Control System (TACACS+) Delivers an authentication tool using TCP with encryption of the full authentication request, providing additional security
- Unicast Reverse Path Forwarding (URPF)
Allows normal packets to be forwarded correctly but discards the attaching packet due to lack of reverse path route or incorrect inbound interface; prevents source spoofing and distributed attacks
- Network login
Allows authentication of multiple users per port
- RADIUS
Eases security access administration by utilizing a user/password authentication server
- Network address translation (NAT)
Supports one-to-one NAT, many-to-many NAT, and NAT control, enabling NAT-PT to support multiple connections; supports deny list in NAT/NAT-PT, a limit on the number of connections, session logs, and multi-instances
- Secure shell (SSHv2)
Uses external servers to securely log in to a remote device. With authentication and encryption, it protects against IP spoofing and plain text password interception; increases the security of SFTP transfers



Convergence

- Internet Group Management Protocol (IGMP)
Utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks; supports IGMPv1, v2, and v3
- Protocol Independent Multicast (PIM)
Defines modes of internet IPv4 and IPv6 multicasting to allow one-to-many and many-to-many transmission of information; supports PIM Dense Mode (DM), Sparse Mode (SM), and Source-Specific Multicast (SSM)
- Multicast Source Discovery Protocol (MSDP)
Allows multiple PIM-SM domains to interoperate; is used for interdomain multicast applications
- Multicast Border Gateway Protocol (MBGP)
Allows multicast traffic to be forwarded across BGP networks and kept separate from unicast traffic

Integration

- Embedded NetStream
Improves traffic distribution using powerful scheduling algorithms, including Layer 4 to 7 services; monitors the health status of servers and firewalls
- Embedded VPN and firewall
Provides enhanced stateful packet inspection and filtering; delivers advanced VPN services with Triple DES (3DES) and Advanced Encryption Standard (AES) encryption at high performance and low latency, URL filtering, and application prioritization and enhancement
- SIP trunking
Delivers multiple concurrent calls on one link; the carrier authenticates only the link rather than carrying each SIP call on the link

Resiliency and high availability

- Backup center
Acts as a part of the management and backup function to provide backup for device interfaces; delivers reliability by switching traffic over to a backup interface when the primary one fails
- Virtual Router Redundancy Protocol (VRRP)
Allows groups of two routers to dynamically back each other up to create highly available routed environments; supports VRRP load balancing
- Embedded Automation Architecture (EAA)
Monitors the internal event and status of system hardware and software, identifying potential problems as early as possible; collects field information and attempts to automatically repair the issues; based on the user configuration, on-site information will be sent to technical support
- Bidirectional Forwarding Detection (BFD)
Quickly detects the failures of the bidirectional forwarding paths between two devices for upper-layer protocols such as routing protocols and MPLS

Management

- HPE Intelligent Management Center (IMC)
Integrates fault management, element configuration, and network monitoring from a central vantage point. Built-in support for third-party devices enables network administrators to centrally manage all network elements with a variety of automated tasks, including discovery, categorization, baseline configurations, and software images. The software also provides configuration comparison tools, version tracking, change alerts, and more
- Industry-standard CLI with a hierarchical structure
Reduces training time and expenses and increases productivity in multivendor installations
- Management security
Restricts access to critical configuration commands; offers multiple privilege levels with password protection. ACLs provide Telnet and SNMP access. Local and remote syslog capabilities allow logging of all access
- SNMPv1, v2, and v3
Provide complete support for SNMP; provide full support for industry-standard Management Information Base (MIB) plus private extensions. SNMPv3 supports increased security using encryption
- Remote monitoring (RMON)
Uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group



- FTP, TFTP, and SFTP support
Offers different mechanisms for configuration updates. FTP allows bidirectional transfers over a TCP/IP network. Trivial FTP (TFTP) is a simpler method using User Datagram Protocol (UDP). Secure File Transfer Protocol (SFTP) runs over an SSH tunnel to provide additional security
- Debug and sampler utility
Supports ping and traceroute for both IPv4 and IPv6
- Network Time Protocol (NTP)
Synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- Information center
Provides a central repository for system and network information; aggregates all logs, traps, and debugging information generated by the system and maintains them in order of severity; outputs the network information to multiple channels based on user-defined rules
- Management interface control
Provides management access through modem port and terminal interface; provides access through terminal interface, Telnet, or SSH
- Network Quality Analyzer (NQA)
Analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays; allows network manager to determine overall network performance and diagnose and locate network congestion points or failures
- Role-based security
Delivers role-based access control (RBAC); supports 16 user levels (0–15)
- Standards-based authentication support for LDAP
Integrates seamlessly into existing authentication services

Ease of deployment

- Zero-touch deployment
Supports both USB disk auto-deployment and 3G SMS auto-deployment

Additional information

- OPEX savings
Simplifies and streamlines deployment, management, and training through the use of a common operating system, thereby cutting costs as well as reducing the risk of human errors associated with having to manage multiple operating systems across different platforms and network layers
- Faster time to market
Allows new and custom features to be brought rapidly to market through engineering efficiencies, delivering better initial and ongoing stability
- Green initiative support
Provides support for RoHS and WEEE regulations

Investment protection

- Reuse of existing SIC modules
Supports existing SIC modules, transceivers, and cables for investment protection

Warranty and support

For details on Limited Lifetime warranty and software releases available with your product purchase, please refer to [hpe.com/networking/support](https://www.hpe.com/networking/support)



HPE MSR2000 Router Series



Specifications

HPE MSR2003X AC Router (SOP10A)

I/O ports and slots 3 fixed 10GbE SFP+ ports, 2 combo ports (SFP or RJ45) and 8 RJ-45 autosensing 10/100/1000 LAN ports

Additional ports and slots 1 RJ45 console port and 1 USB port 2.0 or 3.0

Physical characteristics

Dimensions (w x d x h) 360x300x44.2 mm
 Weight 3.1 kg
 Memory and processor Marvell ARM64 @ 2.2 GHz, 4 GB DRAM, 4 GB eMMC Flash
 Mounting and enclosure Mounts in an EIA standard 19-inch telco rack or equipment cabinet

Performance

Throughput 4 Mpps
 Routing table size 300000 entries (IPv4), 300000 entries (IPv6)
 Forwarding table size 300000 entries (IPv4), 300000 entries (IPv6)

Environment

Operating temperature 0~45°C
 Operating relative humidity 5~95% **no** dew
 Non-operating/storage temp -40°C~70°C
 Non-operating/storage relative humidity 5~95% **no** dew
 Acoustic 37dBA
 Altitude Up to 5,000 ft (1.5 km)

Electrical characteristics

Frequency 2.2 GHz
 Voltage 100~240 VAC; ~50/60 Hz
 Maximum power rating 54W
 Reliability—MTBF (years) 130 years
 Safety IKE/IP
 SecVPN, ADVPN, GDVPN, L2TP VPN, GRE VPN
 NAT/NAPT, PKI, RSA, URPF
 DDoS attack prevention, ARP attack prevention
 EAD
 FIPS, N
 ETCONF, OpenFlow, telemetry, VXLAN, EVPN



HPE MSR2000 Router Series (continued)

Specifications

HPE MSR2003X AC Router (SOP10A)

Electrical characteristics

EMC	<ul style="list-style-type: none"> CISPR 24 EN 55024 EN 61000-3-2 EN 61000-3-3 EN 61000-6-1 ETSI EN 300 386 EN 301 489-1 EN 301 489-17 UL 60950-1 CAN/CSA C22.2 No 60950-1 IEC 60950-1 EN 60950-1/A11
-----	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Telecom

EN 301 511; EN 301 908-1; EN 300 328; EN 62311;
FCC Part 22

Management

IMC—Intelligent Management Center; Command-line interface; SNMP manager; Telnet; RMON1; FTP;
IEEE 802.3 Ethernet MIB

Services

Refer to the Hewlett Packard Enterprise website at hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.



HPE MSR2000 Router Series (continued)



Specifications	HPE MSR2003 AC Router (JG411A)
Ports	3 SIC slots or 1 DSIC slot and 1 SIC slot 2 RJ-45 1000BASE-T ports (IEEE 802.3ab Type 1000BASE-T)
Physical characteristics	
Dimensions	14.17 in. x 11.81 in. x 1.74 in. (w x d x h) (36 cm x 30 cm x 4.42 cm) (1U height)
Weight	7.61 lb (3.45 kg)
Memory and processor	RISC @ 800 MHz, 256 MB flash capacity, 1 GB DDR3 SDRAM
Mounting	Desktop or can be mounted in an EIA standard 19 inch telco rack when used with the rack-mount kit in the package
Performance	
Throughput	Up to 1 Mpps (64-byte packets)
Routing table size	200,000 entries (IPv4), 200,000 entries (IPv6)
Forwarding table size	200,000 entries (IPv4), 200,000 entries (IPv6)
Environment	
Operating temperature	32°F to 113°F (0°C to 45°C)
Operating relative humidity	5% to 90%, noncondensing
Nonoperating/storage temperature	-40°F to 158°F (-40°C to 70°C)
Nonoperating/storage relative humidity	5% to 90%, noncondensing
Altitude	Up to 16,404 ft (5 km)
Electrical characteristics	
Maximum heat dissipation	78 BTU/hr (82.29 kJ/hr)
Voltage	100-120/200-240 VAC
Maximum power rating	54W
Frequency	50/60 Hz
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Reliability	
MTBF (years)	92.73
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J
Emissions	EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000 4-11:2004; EN 61000-4-8:2001
Telecom	FCC part 68; CS-03
Management	HPE IMC; command-line interface; limited command-line interface; configuration menu; out-of-band management (RJ-45 Ethernet); SNMP Manager; Telnet; RMON1; FTP; in-line and out-of-band; modem interface; out-of-band management (serial RS-232C or micro USB); IEEE 802.3 Ethernet MIB



HPE MSR2000 Router Series (continued)

Specifications	HPE MSR2003 AC Router (JG411A)
Services	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour on-site, 13x5 coverage for hardware (UW076E) 3-year, 4-hour on-site, 24x7 coverage for hardware (UW006E) 3-year, 4-hour on-site, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour on-site, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour on-site, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour on-site, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour on-site, 13x5 coverage for hardware (UW077E) 4-year, 4-hour on-site, 24x7 coverage for hardware (UW007E) 4-year, 4-hour on-site, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour on-site, 13x5 coverage for hardware (UW078E) 5-year, 4-hour on-site, 24x7 coverage for hardware (UW008E) 5-year, 4-hour on-site, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair On-site (UW079E) 4 Yr 6 hr Call-to-Repair On-site (UW080E) 5 Yr 6 hr Call-to-Repair On-site (UW081E) 1-year, 6-hour Call-To-Repair On-site for hardware (HR558E) 1-year, 24x7 software phone support, software updates (HR557E)
	See the Hewlett Packard Enterprise website at hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, contact your local HPE sales office.

Standards and protocols
(applies to all products in series)

BGP	RFC 1163 Border Gateway Protocol (BGP) RFC 1267 Border Gateway Protocol 3 (BGP-3) RFC 1657 Definitions of Managed Objects for BGPv4 RFC 1771 BGPv4 RFC 1772 Application of the BGP RFC 1773 Experience with the BGP-4 Protocol RFC 1774 BGP-4 Protocol Analysis RFC 1965 BGP-4 confederations RFC 1997 BGP Communities Attribute RFC 1998 PPP Gandalf FZA Compression Protocol RFC 2439 BGP Route Flap Damping	RFC 2547 BGP/MPLS VPNs RFC 2796 BGP Route Reflection RFC 2842 Capability Advertisement with BGP-4 RFC 2858 Multi-protocol Extensions for BGP-4 RFC 2918 Route Refresh Capability RFC 3065 Autonomous System Confederations for BGP RFC 3107 Support BGP carry label for MPLS RFC 3392 Capabilities Advertisement with BGP-4 RFC 4271 A Border Gateway Protocol 4 (BGP-4)	RFC 4273 Definitions of Managed Objects for BGP-4 RFC 4274 BGP-4 Protocol Analysis RFC 4275 BGP-4 MIB Implementation Survey RFC 4276 BGP-4 Implementation Report RFC 4277 Experience with the BGP-4 Protocol RFC 4360 BGP Extended Communities Attribute RFC 4456 BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP) RFC 4724 Graceful Restart Mechanism for BGP
Denial of service protection	CPU DoS Protection	Rate Limiting by ACLs	
Device management	RFC 1155 Structure and Mgmt. Information (SMIv1) RFC 1157 SNMPv1/v2c RFC 1305 NTPv3 RFC 1591 DNS (client)	RFC 1902 SNMPv2 RFC 1908 SNMPv1/2 Coexistence RFC 1945 Hypertext Transfer Protocol—HTTP/1.0 RFC 2271 Framework RFC 2573 SNMPv3 Applications	RFC 2576 Coexistence between SNMPv1, v2, v3 RFC 2578-2580 SMIv2 RFC 2579 SMIv2 Text Conventions RFC 2580 SMIv2 Conformance RFC 3416 SNMP Protocol Operations v2



Standards and protocols (continued)

(applies to all products in series)

General protocols

RFC 768 UDP	RFC 1827 IP Encapsulating Security Payload (ESP)	RFC 2784 Generic Routing Encapsulation (GRE)
RFC 783 TFTP Protocol (revision 2)	RFC 1829 The ESP DES-CBC Transform	RFC 2827 Network Ingress Filtering: Defeating Denial of Service Attacks Which Employ IP Source Address Spoofing
RFC 791 IP	RFC 1945 Hypertext Transfer Protocol—HTTP/1.0	RFC 2865 Remote Authentication Dial-In User Service (RADIUS)
RFC 792 ICMP	RFC 1966 BGP Route Reflection An alternative to full mesh IBGP	RFC 2866 RADIUS Accounting
RFC 793 TCP	RFC 1981 Path MTU Discovery for IP version 6	RFC 2868 RADIUS Attributes for Tunnel Protocol Support
RFC 826 ARP	RFC 2003 IP Encapsulation within IP	RFC 2869 RADIUS Extensions
RFC 896 Congestion Control in IP/TCP Internetworks	RFC 2018 TCP Selective Acknowledgement Options	RFC 2884 Performance Evaluation of Explicit Congestion Notification (ECN) in IP Networks.
RFC 917 Internet Subnets	RFC 2082 RIP-2 MD5 Authentication	RFC 2963 A Rate Adaptive Shaper for Differentiated Services
RFC 925 Multi-LAN Address Resolution	RFC 2104 HMAC: Keyed-Hashing for Message Authentication	RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS
RFC 950 Internet Standard Subnetting Procedure	RFC 2131 DHCP	RFC 2973 IS-IS Mesh Groups
RFC 951 BOOTP	RFC 2132 DHCP Options and BOOTP Vendor Extensions	RFC 2993 Architectural Implications of NAT
RFC 959 File Transfer Protocol (FTP)	RFC 2138 Remote Authentication Dial-In User Service (RADIUS)	RFC 3011 The IPv4 Subnet Selection Option for DHCP
RFC 1027 Proxy ARP	RFC 2236 IGMP Snooping	RFC 3022 Traditional IP Network Address Translator (Traditional NAT)
RFC 1048 BOOTP Vendor Information Extensions	RFC 2246 The TLS Protocol Version 1.0	RFC 3027 Protocol Complications with the IP Network Address Translator
RFC 1058 RIPv1	RFC 2251 Lightweight Directory Access Protocol (v3)	RFC 3031 Multiprotocol Label Switching Architecture
RFC 1091 Telnet Terminal-Type Option	RFC 2252 Lightweight Directory Access Protocol (v3): Attribute Syntax Definitions	RFC 3032 MPLS Label Stack Encoding
RFC 1093 NSFNET routing architecture	RFC 2283 MBGP	RFC 3036 LDP Specification
RFC 1141 Incremental updating of the Internet checksum	RFC 2309 Recommendations on queue management and congestion avoidance in the Internet	RFC 3037 LDP Applicability
RFC 1142 OSI IS-IS Intra-domain Routing Protocol	RFC 2338 VRRP	RFC 3046 DHCP Relay Agent Information Option
RFC 1166 Internet address used by Internet Protocol (IP)	RFC 2451 The ESP CBC-Mode Cipher Algorithms	RFC 3063 MPLS Loop Prevention Mechanism
RFC 1191 Path MTU discovery	RFC 2453 RIPv2	RFC 3137 OSPF Stub Router Advertisement
RFC 1195 OSI ISIS for IP and Dual Environments	RFC 2474 Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers	RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
RFC 1213 Management Information Base for Network Management of TCP/IP-based Internets	RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols	RFC 3215 LDP State Machine
RFC 1253 OSPF v2	RFC 2519 A Framework for Inter-Domain Route Aggregation	RFC 3246 Expedited Forwarding PHB
RFC 1305 NTPv3 (IPv4 only)	RFC 2529 Transmission of IPv6 over IPv4 Domains without Explicit Tunnels	RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
RFC 1321 The MD5 Message-Digest Algorithm	RFC 2548 MS-RAS-Vendor only	RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 1323 TCP Extensions for High-Performance	RFC 2581 TCP Congestion Control	RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 1349 Type of Service	RFC 2597 Assured Forwarding PHB Group	RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 1350 TFTP Protocol (revision 2)	RFC 2598 An Expedited Forwarding PHB	RFC 3319 Dynamic Host Configuration Protocol (DHCPv6) Options for Session Initiation Protocol (SIP) Servers
RFC 1449 Transport Mappings for version 2 of the Simple Network Management Protocol (SNMPv2)	RFC 2616 HTTP Compatibility v1.1	RFC 3359 Reserved Type, Length and Value (TLV) Codepoints in Intermediate System to Intermediate System
RFC 1519 CIDR	RFC 2661 L2TP	RFC 3392 Support BGP capabilities advertisement
RFC 1542 BOOTP Extensions	RFC 2663 NAT Terminology and Considerations	RFC 3443 Time To Live (TTL) Processing in Multi-Protocol Label Switching (MPLS) Networks
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol	RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)	
RFC 1624 Incremental Internet Checksum	RFC 2698 A Two Rate Three Color Marker	
RFC 1631 NAT	RFC 2716 PPP EAP TLS Authentication Protocol	
RFC 1701 Generic Routing Encapsulation	RFC 2747 RSVP Cryptographic Authentication	
RFC 1702 Generic Routing Encapsulation over IPv4 networks	RFC 2763 Dynamic Name-to-System ID mapping	
RFC 1721 RIP Version 2 Protocol Analysis		
RFC 1722 RIP Version 2 Protocol Applicability Statement		
RFC 1723 RIP Version 2		
RFC 1724 RIP Version 2 MIB Extension		
RFC 1777 Lightweight Directory Access Protocol		
RFC 1812 IPv4 Routing		
RFC 1825 Security Architecture for the Internet Protocol		
RFC 1826 IP Authentication Header		



Standards and protocols (continued)

(applies to all products in series)

General protocols (continued)

<p>RFC 3478 Graceful Restart Mechanism for Label Distribution Protocol</p> <p>RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)</p> <p>RFC 3509 OSPF ABR Behavior</p> <p>RFC 3526 More Modular Exponential (MODP) Diffie-Hellman groups for Internet Key Exchange (IKE)</p> <p>RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering</p> <p>RFC 3567 Intermediate System to Intermediate System (IS-IS) Cryptographic Authentication</p> <p>RFC 3584 Coexistence between Version 1 and Version 2 of the Internet-standard Network Management Framework</p> <p>RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec</p> <p>RFC 3612 Applicability Statement for Restart Mechanisms for the Label Distribution Protocol (LDP)</p> <p>RFC 3623 Graceful OSPF Restart</p> <p>RFC 3646 DNS Configuration options for Dynamic Host Configuration Protocol for IPv6 (DHCPv6)</p> <p>RFC 3662 A Lower Effort Per-Domain Behavior (PDB) for Differentiated Services</p> <p>RFC 3704 Unicast Reverse Path Forwarding (URPF)</p> <p>RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers</p> <p>RFC 3719 Recommendations for Interoperable Networks using Intermediate System to Intermediate System (IS-IS)</p> <p>RFC 3736 Stateless Dynamic Host Configuration Protocol (DHCP) Service for IPv6</p> <p>RFC 3768 Virtual Router Redundancy Protocol (VRRP)</p> <p>RFC 3782 The NewReno Modification to TCP's Fast Recovery Algorithm</p> <p>RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit</p> <p>RFC 3787 Recommendations for Interoperable IP Networks using Intermediate System to Intermediate System (IS-IS)</p> <p>RFC 3810 Multicast Listener Discovery Version 2 (MLDv2) for IPv6</p> <p>RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)</p> <p>RFC 3815 Definitions of Managed Objects for the Multiprotocol Label Switching (MPLS), Label Distribution Protocol (LDP)</p> <p>RFC 3847 Restart signaling for IS-IS</p>	<p>RFC 3916 Requirements for Pseudowire Emulation Edge-to-Edge (PWE3)</p> <p>RFC 3948 UDP Encapsulation of IPsec ESP Packets</p> <p>RFC 3973 Protocol Independent Multicast—Dense Mode (PIM-DM): Protocol Specification (Revised)</p> <p>RFC 3985 Pseudowire Emulation Edge-to-Edge (PWE3) Architecture</p> <p>RFC 4061 Benchmarking Basic OSPF Single Router Control Plane Convergence</p> <p>RFC 4062 OSPF Benchmarking Terminology and Concepts</p> <p>RFC 4063 Considerations When Using Basic OSPF Convergence Benchmarks</p> <p>RFC 4109 Algorithms for Internet Key Exchange version 1 (IKEv1)</p> <p>RFC 4133 Entity MIB (Version 3)</p> <p>RFC 4182 Removing a Restriction on the use of MPLS Explicit NULL Addressing Protocol (ISATAP)</p> <p>RFC 4222 Prioritized Treatment of Specific OSPF Version 2 Packets and Congestion Avoidance</p> <p>RFC 4250 The Secure Shell (SSH) Protocol Assigned Numbers</p> <p>RFC 4251 The Secure Shell (SSH) Protocol Architecture</p> <p>RFC 4252 The Secure Shell (SSH) Authentication Protocol</p> <p>RFC 4253 The Secure Shell (SSH) Transport Layer Protocol</p> <p>RFC 4254 The Secure Shell (SSH) Connection Protocol</p> <p>RFC 4291 IP Version 6 Addressing Architecture</p> <p>RFC 4305 Cryptographic Algorithm Implementation Requirements for Encapsulating Security Payload (ESP) and Authentication Header (AH)</p> <p>RFC 4364 BGP/MPLS IP Virtual Private Networks (VPNs)</p> <p>RFC 4365 Applicability Statement for BGP/MPLS IP Virtual Private Networks (VPNs)</p> <p>RFC 4381 Analyses of the Security of BGP/MPLS IP VPNs</p> <p>RFC 4382 MPLS/BGP Layer 3 Virtual Private Network (VPN) Management Information Base</p> <p>RFC 4385 Pseudowire Emulation Edge-to-Edge (PWE3) Control Word for Use over an MPLS PSN</p> <p>RFC 4419 Diffie-Hellman Group Exchange for the Secure Shell (SSH) Transport Layer Protocol</p> <p>RFC 4446 IANA Allocations for Pseudowire Edge to Edge Emulation (PWE3)</p> <p>RFC 4447 Pseudowire Setup and Maintenance Using the Label Distribution Protocol (LDP)</p>	<p>RFC 4448 Encapsulation Methods for Transport of Ethernet over MPLS Networks</p> <p>RFC 4451 BGP MULTI_EXIT_DISC (MED) Considerations</p> <p>RFC 4486 Subcodes for BGP Cease Notification Message</p> <p>RFC 4541 Considerations for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) Snooping Switches</p> <p>RFC 4553 Structure-Agnostic Time Division Multiplexing (TDM) over Packet (SAToP)</p> <p>RFC 4562 MAC-Forced Forwarding: A Method for Subscriber Separation on an Ethernet Access Network</p> <p>RFC 4576 Using a Link State Advertisement (LSA) Options Bit to Prevent Looping in BGP/MPLS IP Virtual Private Networks (VPNs)</p> <p>RFC 4577 OSPF as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks (VPNs)</p> <p>RFC 4594 Configuration Guidelines for DiffServ Service Classes</p> <p>RFC 4601 Protocol Independent Multicast—Sparse Mode (PIM-SM): Protocol Specification (Revised)</p> <p>RFC 4618 Encapsulation Methods for Transport of PPP/High-Level Data Link Control (HDLC) over MPLS Networks</p> <p>RFC 4619 Encapsulation Methods for Transport of Frame Relay over Multiprotocol Label Switching (MPLS) Networks</p> <p>RFC 4632 Classless Inter-domain Routing (CIDR): The Internet Address Assignment and Aggregation Plan</p> <p>RFC 4659 BGP/MPLS IP Virtual Private Network (VPN) Extension for IPv6 VPN</p> <p>RFC 4664 Framework for Layer 2 Virtual Private Networks (L2VPNs)</p> <p>RFC 4665 Service Requirements for Layer 2 Provider-Provisioned Virtual Private Networks</p> <p>RFC 4741 NETCONF Configuration Protocol</p> <p>RFC 4742 Using the NETCONF Configuration Protocol over Secure Shell (SSH)</p> <p>RFC 4743 Using NETCONF over the Simple Object Access Protocol (SOAP)</p> <p>RFC 4765 Service Requirements for Layer 2 Provider-Provisioned Virtual Private Networks</p> <p>RFC 4781 Graceful Restart Mechanism for BGP with MPLS</p> <p>RFC 4787 Network Address Translation (NAT) Behavioral Requirements for Unicast UDP</p> <p>RFC 4798 Connecting IPv6 Islands over IPv4 MPLS Using IPv6 Provider Edge Routers (6PE)</p> <p>RFC 4811 OSPF Out-of-Band Link State Database (LSDB) Resynchronization</p> <p>RFC 4812 OSPF Restart Signaling</p>
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



Standards and protocols (continued)

(applies to all products in series)

General protocols (continued)	<p>RFC 4813 OSPF Link-Local Signaling</p> <p>RFC 4816 Pseudowire Emulation Edge-to-Edge (PWE3) Asynchronous Transfer Mode (ATM) Transparent Cell Transport Service</p> <p>RFC 4835 Cryptographic Algorithm Implementation Requirements for Encapsulating Security Payload (ESP) and Authentication Header (AH)</p> <p>RFC 4861 Neighbor Discovery for IP version 6 (IPv6)</p> <p>RFC 4862 IPv6 Stateless Address Autoconfiguration</p> <p>RFC 4878 Definitions and Managed Objects for Operations, Administration, and Maintenance (OAM) Functions on</p> <p>RFC 4893 BGP Support for Four-octet AS Number Space</p> <p>RFC 4940 IANA Considerations for OSPF</p> <p>RFC 4941 Privacy Extensions for Stateless Address Autoconfiguration in IPv6</p> <p>RFC 5007 DHCPv6 Leasequery</p> <p>RFC 5036 LDP Specification</p> <p>RFC 5065 Autonomous System Confederations for BGP</p> <p>RFC 5086 Structure-Aware Time Division Multiplexed (TDM) Circuit Emulation Service over Packet Switched Network (CESoPSN)</p> <p>RFC 5095 Deprecation of Type 0 Routing Headers in IPv6</p>	<p>RFC 5130 A Policy Control Mechanism in IS-IS Using Administrative Tags</p> <p>RFC 5187 OSPFv3 Graceful Restart</p> <p>RFC 5214 Intra-Site Automatic Tunnel Addressing Protocol (ISATAP)</p> <p>RFC 5254 Requirements for Multi-Segment Pseudowire Emulation Edge-to-Edge (PWE3)</p> <p>RFC 5277 NETCONF Event Notifications</p> <p>RFC 5280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile</p> <p>RFC 5286 Basic Specification for IP Fast Reroute: Loop-Free Alternates</p> <p>RFC 5287 Control Protocol Extensions for the Setup of Time-Division Multiplexing (TDM) Pseudowires in MPLS Networks</p> <p>RFC 5301 Dynamic Hostname Exchange Mechanism for IS-IS</p> <p>RFC 5302 Domain-Wide Prefix Distribution with Two-Level IS-IS</p> <p>RFC 5304 Intermediate System to Intermediate System (IS-IS) Cryptographic Authentication</p> <p>RFC 5306 Restart Signaling for IS-IS</p> <p>RFC 5308 Routing IPv6 with IS-IS</p> <p>RFC 5309 Point-to-Point Operation over LAN in Link State Routing Protocols</p>	<p>RFC 5381 Experience of Implementing NETCONF over SOAP</p> <p>RFC 5382 The IP Network Address Translator (NAT)</p> <p>RFC 5398 Autonomous System (AS) Number Reservation for Documentation Use</p> <p>RFC 5492 Capabilities Advertisement with BGP-4</p> <p>RFC 5508 NAT Behavioral Requirements for ICMP</p> <p>RFC 5539 NETCONF over Transport Layer Security (TLS)</p> <p>RFC 5613 OSPF Link-Local Signaling</p> <p>RFC 5659 An Architecture for Multi-Segment Pseudowire Emulation Edge-to-Edge</p> <p>RFC 5798 Virtual Router Redundancy Protocol (VRRP) Version 3 for IPv4 and IPv6</p> <p>RFC 5880 Bidirectional Forwarding Detection</p> <p>RFC 5881 BFD for IPv4 and IPv6 (Single Hop)</p> <p>RFC 5882 Generic Application of BFD</p> <p>RFC 5883 BFD for Multihop Paths</p> <p>RFC 5905 Network Time Protocol Version 4: Protocol and Algorithms Specification</p> <p>RFC 854 Telnet Protocol Specification</p> <p>RFC 856 Telnet Binary Transmission</p>
IP multicast	<p>RFC 1112 IGMP</p> <p>RFC 2362 PIM Sparse Mode</p>	<p>RFC 2710 Multicast Listener Discovery (MLD) for IPv6</p> <p>RFC 2934 Protocol Independent Multicast MIB for IPv4</p> <p>RFC 3376 IGMPv3</p>	<p>RFC 3376 IGMPv3 (host joins only)</p> <p>RFC 5059 Bootstrap Router (BSR) Mechanism for Protocol Independent Multicast (PIM)</p>
IPv6	<p>RFC 2080 RIPng for IPv6</p> <p>RFC 2460 IPv6 Specification</p> <p>RFC 2473 Generic Packet Tunneling in IPv6</p> <p>RFC 2475 IPv6 DiffServ Architecture</p>	<p>RFC 2529 Transmission of IPv6 Packets over IPv4</p> <p>RFC 2545 Use of MP-BGP-4 for IPv6</p> <p>RFC 2553 Basic Socket Interface Extensions for IPv6</p> <p>RFC 2740 OSPFv3 for IPv6</p>	<p>RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers</p> <p>RFC 3056 Connection of IPv6 Domains via IPv4 Clouds</p> <p>RFC 3162 RADIUS and IPv6</p> <p>RFC 3315 DHCPv6 (client and relay)</p> <p>RFC 5340 OSPF for IPv6</p>
MIBs	<p>RFC 1213 MIB II</p> <p>RFC 1493 Bridge MIB</p> <p>RFC 1724 RIPv2 MIB</p> <p>RFC 1850 OSPFv2 MIB</p> <p>RFC 1907 SNMPv2 MIB</p> <p>RFC 2011 SNMPv2 MIB for IP</p>	<p>RFC 2012 SNMPv2 MIB for TCP</p> <p>RFC 2013 SNMPv2 MIB for UDP</p> <p>RFC 2096 IP Forwarding Table MIB</p> <p>RFC 2233 Interfaces MIB</p> <p>RFC 2273 SNMP-NOTIFICATION-MIB</p> <p>RFC 2571 SNMP Framework MIB</p> <p>RFC 2572 SNMP-MPD MIB</p>	<p>RFC 2573 SNMP-Notification MIB</p> <p>RFC 2574 SNMP USM MIB</p> <p>RFC 2674 802.1p and IEEE 802.1Q Bridge MIB</p> <p>RFC 2737 Entity MIB (Version 2)</p> <p>RFC 2863 The Interfaces Group MIB</p> <p>RFC 3813 MPLS LSR MIB</p>



Standards and protocols (continued)

(applies to all products in series)

Network management	<p>IEEE 802.1D (STP) RFC 1098 Simple Network Management Protocol (SNMP) RFC 1158 Management Information Base for network management of TCP/IP-based Internets: MIB-II RFC 1212 Concise MIB definitions RFC 1215 Convention for defining traps for use with the SNMP RFC 1389 RIPv2 MIB Extension RFC 1448 Protocol Operations for version 2 of the Simple Network Management Protocol (SNMPv2) RFC 1450 Management Information Base (MIB) for version 2 of the Simple Network Management Protocol (SNMPv2) RFC 1902 Structure of Management Information for Version 2 of the Simple Network Management Protocol (SNMPv2) RFC 1903 SNMPv2 Textual Conventions</p>	<p>RFC 1904 SNMPv2 Conformance RFC 1905 SNMPv2 Protocol Operations RFC 1906 SNMPv2 Transport Mappings RFC 1908 Coexistence between Version 1 and Version 2 of the Internet-standard Network Management Framework RFC 1918 Private Internet Address Allocation RFC 2037 Entity MIB using SMIv2 RFC 2261 An Architecture for Describing SNMP Management Frameworks RFC 2262 Message Processing and Dispatching for the Simple Network Management Protocol (SNMP) RFC 2263 SNMPv3 Applications RFC 2264 User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3) RFC 2265 View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)</p>	<p>RFC 2272 SNMPv3 Management Protocol RFC 2273 SNMPv3 Applications RFC 2274 USM for SNMPv3 RFC 2275 VACM for SNMPv3 RFC 2575 SNMPv3 View-based Access Control Model (VACM) RFC 3164 BSD Syslog Protocol RFC 3411 An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks RFC 3412 Message Processing and Dispatching for the Simple Network Management Protocol (SNMP) RFC 3413 Simple Network Management Protocol (SNMP) Applications RFC 3414 SNMPv3 User-based Security Model (USM) RFC 3415 View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)</p>
OSPF	<p>RFC 1245 OSPF protocol analysis RFC 1246 Experience with OSPF</p>	<p>RFC 1583 OSPFv2 RFC 1587 OSPF NSSA RFC 1765 OSPF Database Overflow</p>	<p>RFC 1850 OSPFv2 Management Information Base (MIB), traps RFC 2328 OSPFv2 RFC 2370 OSPF Opaque LSA Option</p>
QoS/CoS	<p>IEEE 802.1P (CoS) RFC 2474 DS Field in the IPv4 and IPv6 Headers RFC 2475 DiffServ Architecture</p>	<p>RFC 2597 DiffServ Assured Forwarding (AF) RFC 2598 DiffServ Expedited Forwarding (EF) RFC 2697 A Single Rate Three Color Marker</p>	<p>RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP RFC 3247 Supplemental Information for the New Definition of the EF PHB</p>
Security	<p>IEEE 802.1X Port-Based Network Access Control RFC 2082 RIP-2 MD5 Authentication RFC 2104 Keyed-Hashing for Message Authentication RFC 2138 RADIUS Authentication RFC 2139 RADIUS Accounting</p>	<p>RFC 2408 Internet Security Association and Key Management Protocol (ISAKMP) RFC 2409 The Internet Key Exchange (IKE) RFC 2412 The OAKLEY Key Determination Protocol RFC 2459 Internet X.509 Public Key Infrastructure Certificate and CRL Profile</p>	<p>RFC 2818 HTTP Over TLS RFC 2865 RADIUS Authentication RFC 2866 RADIUS Accounting RFC 3579 RADIUS Support For Extensible Authentication Protocol (EAP) RFC 3580 IEEE 802.1X Remote Authentication Dial-In User Service (RADIUS) Usage Guidelines</p>
VPN	<p>RFC 1828 IP Authentication using Keyed MD5 RFC 1853 IP in IP Tunneling RFC 2401 Security Architecture for the Internet Protocol RFC 2402 IP Authentication Header RFC 2403 The Use of HMAC-MD5-96 within ESP and AH RFC 2404 The Use of HMAC-SHA-1-96 within ESP and AH</p>	<p>RFC 2405 The ESP DES-CBC Cipher Algorithm With Explicit IV RFC 2406 IP Encapsulating Security Payload (ESP) RFC 2407 The Internet IP Security Domain of Interpretation for ISAKMP RFC 2410 The NULL Encryption Algorithm and Its Use With IPSec RFC 2411 IP Security Document Roadmap</p>	<p>RFC 3948 UDP Encapsulation of IPSec ESP Packets RFC 4301 Security Architecture for the Internet Protocol RFC 4302 IP Authentication Header (AH) RFC 4303 IP Encapsulating Security Payload (ESP) RFC 4305 Cryptographic Algorithm Implementation Requirements for ESP and AH</p>



HPE MSR2000 Router Series accessories

Transceivers

HPE X110 100M SFP LC FX Transceiver (JD102B)
HPE X110 100M SFP LC LX Transceiver (JD120B)
HPE X110 100M SFP LC LH40 Transceiver (JD090A)
HPE X110 100M SFP LC LH80 Transceiver (JD091A)
HPE X120 1G SFP LC SX Transceiver (JD118B)
HPE X120 1G SFP LC LX Transceiver (JD119B)
HPE X125 1G SFP LC LH40 1310nm Transceiver (JD061A)
HPE X120 1G SFP LC LH40 1550nm Transceiver (JD062A)
HPE X125 1G SFP LC LH70 Transceiver (JD063B)
HPE X120 1G SFP LC LH100 Transceiver (JD103A)
HPE X120 1G SFP LC BX 10-U Transceiver (JD098B)
HPE X120 1G SFP LC BX 10-D Transceiver (JD099B)
HPE X120 1G SFP RJ45 T Transceiver JD089B
HPE X130 10G SFP+ LC ER 40km XCVR JG234A

Cables

HPE X200 V.24 DTE 3m Serial Port Cable (JD519A)
HPE X200 V.24 DCE 3m Serial Port Cable (JD521A)
HPE X200 V.35 DTE 3m Serial Port Cable (JD523A)
HPE X200 V.35 DCE 3m Serial Port Cable (JD525A)
HPE X200 X.21 DTE 3m Serial Port Cable (JD527A)
HPE X200 X.21 DCE 3m Serial Port Cable (JD529A)
HPE X260 RS449 3m DTE Serial Port Cable (JF825A)
HPE X260 RS449 3m DCE Serial Port Cable (JF826A)
HPE X260 RS530 3m DTE Serial Port Cable (JF827A)
HPE X260 RS530 3m DCE Serial Port Cable (JF828A)
HPE X260 Auxiliary Router Cable (JD508A)
HPE X260 E1 (2) BNC 75 ohm 3m Router Cable (JD175A)
HPE X260 E1 BNC 20m Router Cable (JD514A)
HPE X260 E1 2 BNC 75 ohm 40m Router Cable (JD516A)
HPE X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable (JD511A)
HPE X260 2E1 BNC 3m Router Cable (JD643A)
HPE X260 T1 Router Cable (JD518A)
HPE X260 T1 Voice Router Cable (JD535A)
HPE X260 SIC-8AS RJ45 0.28m Router Cable (JD642A)
HPE X260 mini D-28 to 4-RJ45 0.3m Router Cable (JG263A)
HPE X260 E1 RJ45 to 2xBNC 3m Router Cbl JH294A
HPE X260 E1 RJ45 120 ohm 2m Router Cbl JC156A
HPE X260 E1 RJ45 120 ohm 15m Router Cbl JC151A
HPE X260 E1 RJ45 120 ohm 30m Router Cbl JC152A
HPE MSR 3G RF 2.8m Antenna Cable JG522A
HPE MSR 3G RF 6m Antenna Cable JG666A
HPE MSR 3G RF 15m Antenna Cable JG667A
HPE X240 10G SFP+ SFP+ 1.2m DAC Cable JD096C
HPE X240 10G SFP+ SFP+ 3m DAC Cable JD097C

Router modules

HPE MSR 9-port 10/100Base-T Switch DSIC Module (JD574B)
HPE MSR 4-port 10/100Base-T Switch SIC Module (JD573B)
HPE MSR 1-port 10/100Base-T SIC Module (JD545B)
HPE MSR 1p E1/T1 Voice SIC Mod JH240A
HPE A-MSR 1-port ADSL over POTS SIC Mod JD537A
HPE A MSR 1p 8-wire G.SHDSL DSIC Module JG191A
HPE MSR 1p E1/CE1/PRI SIC Mod JG604A
HPE MSR 4G LTE SIC Mod for Verizon JG742A
HPE MSR 4p Enh Sync/Async Srl SIC Mod JG737A



HPE MSR2000 Router Series accessories (continued)

Router modules (continued)

HPE MSR 1p GbE Combo SIC Mod JG738A
HPE MSR 4p Gig-T Switch SIC Mod JG739A
HPE FlexNetwork MSR 4-port GbE Combo SIC Module R8V29A
HPE MSR 1-port 100Base-X SIC Module (JF280A)
HPE MSR 1-port GbE Combo SIC Module (JD572A)
HPE MSR 2-port FXO SIC Module (JD558A)
HPE MSR 1-port FXO SIC Module (JD559A)
HPE MSR 2-port FXS SIC Module (JD560A)
HPE MSR 1-port FXS SIC Module (JD561A)
HPE MSR 2-port FXS/1-port FXO SIC Module (JD632A)
HPE MSR 4-port FXS/1-port FXO DSIC Module (JG189A)
HPE MSR 2-port ISDN-S/T Voice SIC Module (JF821A)
HPE MSR 1-port E1/Fractional E1 (75ohm) SIC Module (JD634B)
HPE MSR 2-port E1/Fractional E1 (75ohm) SIC Module (JF842A)
HPE MSR 1-port T1/Fractional T1 SIC Module (JD538A)
HPE MSR 1-port Enhanced Sync/Async Serial SIC Module (JD557A)
HPE MSR 1-port ISDN-S/T SIC Module (JD571A)
HPE MSR 8-port Async Serial SIC Module (JF281A)
HPE MSR 16-port Async Serial SIC Module (JG186A)
HPE MSR HSPA/WCDMA SIC Module (JG187A)

Power supplies

HPE X351 150W DC Power Supply JG746A
HPE X351 150W AC Power Supply JG745A

Learn more at

hpe.com/us/en/networking/comware.html

Make the right purchase decision.
Contact our presales specialists.



Chat now (sales)



Call now

Explore **HPE GreenLake**



Get updates


**Hewlett Packard
Enterprise**

© Copyright 2023 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

sFlow is a registered trademark of InMon Corp. All third-party marks are property of their respective owners.

4AA4-8837ENW, Rev. 9