

HPE G2 Metered and Switched Power Distribution Units QuickSpecs

New G2 features allow for greater management of power and environment in IT racks

HPE Enterprise Series G2 Metered and Switched PDUs are designed to work precisely with HPE Infrastructure and Compute solutions, providing a highly accurate (billing-grade accuracy) power distribution solution with outlet-level metering and switching for your IT racks. Designed for use with HPE Standard, Advanced, and Enterprise racks (and compatible with other industry-standard server racks), HPE G2 Metered and Switched PDUs guarantee a compatible fit and reliable operation backed by a 3-year warranty. HPE G2 Metered & Switched PDUs are also rated for operating temperatures up to 60°C, adding an increased level of operational reliability for power distribution in your IT racks.

Overview

A major concern for IT administrators and facility managers is their ability to quickly diagnose and service power related problems in their IT racks. G2 Metered & Switched PDU features such as color-coded outlets and low-profile form factors allow for simple and quick access to IT equipment and power cables in the rear of the rack.

HPE G2 Metered & Switched PDU features are also directly focused on other pain points in the data center. 1Gb Ethernet alleviates the need to maintain older switch solutions that have been traditionally required for PDU network connectivity. High-density outlet configurations that provide up to 48 power outlets in a full-height vertical form factor allow for simple access to power in the rack while minimizing physical cable requirements. Support for up to eight sensors per PDU provides a cost-effective and exhaustive solution for monitoring the environmental elements (temperature, humidity, and leakage) in both the front and rear of the rack.

All G2 Metered & Switched PDU models feature support for the HPE IEC Locking Power Cords, a new supported option available for most HPE G2 PDUs. The IEC Locking Power Cords provide secure cable retention to both the PDU and target device, protecting against vibration during shipping and ensuring that cables are not dislodged during a service event. HPE's IEC Locking Power Cords provide a safe and secure solution against the common issues that lead to power-related downtime.

Why HPE Metered and Switched PDUs?

- HPE Tech Care services purchased for server and storage products, such as extended warranties and premium support services, extend to our PDU products free of charge when purchased together.
- HPE guarantees 100% compatibility between its Rack and Power Infrastructure products and its industry-standard compute, storage, and networking solutions, backed with a 3-year warranty for all G2 Metered PDU models.
- HPE offers multiple Metered PDU form factors that promote efficient use of space in the rack and provide flexibility in how each PDU can be mounted and configured with cables.

Overview

Single-Phase Full-Height Model (P9S15A, P9S18A)**Three-Phase Full-Height Model (P9S21A, P9S24A)****Three-Phase High-Density Outlet Model (P9S23A, P9S25A)****200–208V Input, Single Phase, North America/Japan**

HPE G2 Metered/Switched 4.9kVA/L6-30P 24A/208V Outlets (20) C13 (4) C19/Vertical
NA/JP PDU

P9S15A

200–208V Input, Three Phase, North America/Japan

HPE G2 Metered/Switched 3Ph 8.6kVA/L15-30P 24A/208V Outlets (18) C13 (6) C19/Vertical
NA/JP PDU

P9S19A

HPE G2 Metered/Switched 3Ph 17.3kVA/60309 4-wire 48A/208V Out (12) C13 (12)
C19/Vertical NA/JP PDU

P9S22A

HPE G2 Metered/Switched 3Ph 17.3kVA/60309 4-wire 48A/208V Out (36) C13 (12)
C19/Vertical NA/JP PDU

P9S23A

220–240V Input, Three Phase, International

HPE G2 Metered/Switched 3Ph 11kVA/60309 5-wire 16A/230V Out (18) C13 (6) C19/Vertical
INTL PDU

P9S20A

HPE G2 Metered/Switched 3Ph 22kVA/60309 5-wire 32A/230V Out (36) C13 (12)
C19/Vertical INTL PDU

P9S25A

Standard Features

Power Metering and Management

- All G2 HPE Metered & Switched PDUs meet IEC 62053-21, Class 1 standards for $\pm 1\%$ or better accuracy in outlet-level power metering of:
 - Amperage
 - Voltage
 - Wattage
 - Kilowatts per hour
 - OLED display provides local monitoring and alert indications
 - Remote PDU management and power monitoring supported through integrated web-based user interface, CLI, and third-party software applications supporting SNMP
-

Compatibility

- Designed specifically for use with HPE rack enclosures, but compatible with most 3rd party IT racks
 - Integrated web-based user interface compatible with IPv4/IPv6 and SNMPv1/SNMPv3
-

Usability

- Multiple full-height vertical models with a range of outlet configurations
 - Low-profile form factors ensure integrity of rear-rack keep-out zone for IT maintenance
 - Color-coded receptacles to easily distinguish between the different load segments/phases
 - Integrated cord retention for all IEC C19 and C13 receptacles
 - Optional dual-locking power cords securing both power connections
 - Local and remote firmware updates
-

Security

- Outlet-level on/off power switching that can be accessed locally and remotely
 - Local and LDAP security with multiple access levels
 - Support for HTTP, HTTPS, and SSH protocols
 - Configurable alarm thresholds for both power and environmental monitoring
-

HPE G2 Metered & Switched PDUs support multiple features that are unique to HPE and help to provide the best user experience. Information on these features is summarized below with additional information found online in HPE G2 Metered & Switched PDU User's Guide.

Rated for High Operating Temperatures

Increasing IT densities and escalating operating costs have created a need for rack infrastructure that can operate reliably at higher operating temperatures. HPE G2 PDUs have been designed with high temperature-rated premium components and construction that support increased reliability levels at elevated temperatures. HPE G2 PDUs are rated for operation in temperatures up to 60°C (or 140°F) in the rear of the rack.

Standard Features

IEC Locking Power Cords

HPE G2 PDU models support optional IEC Locking Power Cords with an integrated locking technology on both ends of the cable. HPE Locking Power Cord are available for both C13/14 and C19/20 power receptacles in multiple cable length options, and can be purchased in single or six-pack kits. One IEC Locking Power Cord has been included with each PDU model that supports either a C13 and/or C19 outlet.

High-Density Vertical PDU Models

High-density Vertical PDU models provide 48 outlets in a full-height (42U) form factor. This density is achieved by placing the power receptacles on one side of the PDU and access to the circuit breakers on the opposite side without significantly impacting the height (profile) of the PDU. See the Model Matrix section for more information on high-density PDU models.

Color-Coded Outlets

All HPE G2 PDU models now include color-coded outlets which are highly visible from the rear of the rack. The color-coding helps to easily and clearly identify outlets to simplify cabling and power phase balancing when configuring your IT equipment.

1Gb Ethernet Support

HPE is the first IT solutions company to standardize on 1Gb Ethernet for PDU network connectivity. This eliminates the need to maintain older switching solutions needed for the 10/100 connectivity provided by most other PDU manufacturers.

Environmental Sensors

HPE G2 Metered & Switched PDU models include two environmental sensor ports (can be upgraded to six ports with the addition of up to two G2 PDU Sensor Port Hubs) that can monitor and record up to eight sensor measurements. Multiple sensor options are available providing the ability to monitor temperature, humidity, water leakage, and intrusion for each rack. Please review the Related Options section for a list of the options available.

Flexible Mounting

Most vertical HPE G2 PDU models support mounting on the back and both sides of the PDU using an industry-standard button and keyhole mounting system for easy drop-in installation. This provides a flexible mounting capability that allows power cables to be configured with outlets facing toward the center, back, or front of the rack.

Standard Features

HPE PDU Extension Bar Options

HPE PDU extension bar options help expand the availability of power in the rear of the rack. Each extension bar includes a locking input power cord that connects to the PDU and supports HPE's new IEC Locking Power Cords for C13/C14 and C19/C20 outlets. HPE PDU extension bars can be added to Horizontal and Vertical PDU models, with available C19 outlets, to add additional power outlets and expand access to power in the back of the rack when needed. Extension Bars mount directly to the frame of the rack in multiple locations allowing you the flexibility of placing access to power where it is needed most (see figure above). Multiple extension bar options are available to help you customize the outlet configurations you require extension bars are also compatible with previous generation PDU models that offer C20 outlets (locking feature only supported on new G2 PDU models). See the Related Options section for more information on G2 Extension Bar models.

3-Year Warranty

HPE G2 Metered PDU models are supported with a 3-year warranty. Additionally, the HPE Tech Care Extension program provides additional support and services for your PDU models when purchased with HPE servers, storage, and networking solutions at no additional charge.

Additional information regarding worldwide limited warranty and technical support is available at:

<https://support.hpe.com/connect/s/warrantycheck>

Other related Services

HPE Server Hardware Installation

Provides for the basic hardware installation of HPE branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.

<https://h20195.www2.hpe.com/v2/Getdocument.aspx?docname=5981-9356enw>

HPE Installation and Startup Service

Provides for the installation of your HPE hardware according to product specifications including options. The HPE service delivery technician will connect the product to a LAN as appropriate and enable remote support to allow for automatic case creation for hardware failures. Installation and start up services also includes the installation of one supported operating system type (Windows® or Linux).

DC for Hyperscale

Complete Care for Hyperscale is available for Service Providers and HPC customers who use a scale out approach to computing with a high-volume homogenous infrastructure and resilient architecture can take advantage of this environment support tailored to their operating model.

Standard Features

HPE Factory Express for Servers and storage

HPE Factory Express offers configuration, customization, integration and deployment services for HPE servers and storage products. Customers can choose how their factory solutions are built, tested, integrated, shipped and deployed.

Factory Express offers service packages for simple configuration, racking, installation, complex configuration and design services as well as individual factory services, such as image loading, asset tagging, and custom packaging. HPE products supported through Factory Express include a wide array of servers and storage: HPE Integrity, HPE ProLiant, HPE Apollo, HPE ProLiant Server Blades, HPE BladeSystem, HPE 9000 servers as well as the MSAXxxx3PAR suite, XP, rackable tape libraries and configurable network switches.

HPE Service Credits

HPE Service Credits offers flexible services and technical skills to meet your changing IT demands. With a menu of service that is tailored to suit your needs, you get additional resources and specialist skills to help you maintain peak performance of your IT. Offered as annual credits, you can plan your budgets while proactively responding to your dynamic business.

HPE Education Services

Keep your IT staff trained making sure they have the right skills to deliver on your business outcomes. Book on a class today and learn how to get the most from your technology investment. <http://www.hpe.com/ww/learn>

HPE Support Center

The HPE Support Center is a personalized online support portal with access to information, tools and experts to support HPE business products. Submit support cases online, chat with HPE experts, access support resources or collaborate with peers.

Learn more <http://www.hpe.com/support/hpesc>.

The HPE Support Center Mobile App* allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime.

HPE Insight Remote Support and HPE Support Center are available at no additional cost with a HPE warranty, HPE Support Service or HPE contractual support agreement.

Notes: *HPE Support Center Mobile App is subject to local availability.

For more information: <http://www.hpe.com/services>.

Warranty and Support Services will extend to include HPE options configured with your server or storage device. The price of support service is not impacted by configuration details. HPE sourced options that are compatible with your product will be covered under your server support at the same level of coverage allowing you to upgrade freely. Installation for HPE options is available as needed. To keep support costs low for everyone, some high value options will require additional support. Additional support is only required on select high value workload accelerators, fibre switches, InfiniBand and UPS batteries over 12KVA.

Standard Features

Parts and Materials

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Packard Enterprise due to malfunction.

Service and Support

HPE Services

No matter where you are in your digital transformation journey, you can count on HPE Services to deliver the expertise you need when, where and how you need it. From planning to deployment, ongoing operations and beyond, our experts can help you realize your digital ambitions.

<https://www.hpe.com/services>

Consulting Services

No matter where you are in your journey to hybrid cloud, experts can help you map out your next steps. From determining what workloads should live where, to handling governance and compliance, to managing costs, our experts can help you optimize your operations.

<https://www.hpe.com/services/consulting>

HPE Managed Services

HPE runs your IT operations, providing services that monitor, operate, and optimize your infrastructure and applications, delivered consistently and globally to give you unified control and let you focus on innovation.

[HPE Managed Services | HPE](#)

Operational Services

Optimize your entire IT environment and drive innovation. Manage day-to-day IT operational tasks while freeing up valuable time and resources. Meet service-level targets and business objectives with features designed to drive better business outcomes.

<https://www.hpe.com/services/operational>

HPE Complete Care Service

HPE Complete Care Service is a modular, edge-to-cloud IT environment service designed to help optimize your entire IT environment and achieve agreed upon IT outcomes and business goals through a personalized experience. All delivered by an assigned team of HPE Services experts. HPE Complete Care Service provides:

- A complete coverage approach – edge to cloud
- An assigned HPE team
- Modular and fully personalized engagement
- Enhanced Incident Management experience with priority access
- Digitally enabled and AI driven customer experience

<https://www.hpe.com/services/complecare>

Service and Support

HPE Tech Care Service

HPE Tech Care Service is the operational support service experience for HPE products. The service goes beyond traditional support by providing access to product specific experts, an AI-driven digital experience, and general technical guidance to not only reduce risk but constantly search for ways to do things better. HPE Tech Care Service delivers a customer-centric, AI-driven, and digitally enabled customer experience to move your business forward. HPE Tech Care Service is available in three response levels. Basic, which provides 9x5 business hour availability and a 2-hour response time. Essential which provides a 15-minute response time 24x7 for most enterprise level customers, and Critical which includes a 6-hour repair commitment where available and outage management response for severity 1 incidents.

<https://www.hpe.com/services/techcare>

HPE Lifecycle Services

HPE Lifecycle Services provide a variety of options to help maintain your HPE systems and solutions at all stages of the product lifecycle. A few popular examples include:

- Lifecycle Install and Startup Services: Various levels for physical installation and power on, remote access setup, installation and startup, and enhanced installation services with the operating system.
- HPE Firmware Update Analysis Service: Recommendations for firmware revision levels for selected HPE products, taking into account the relevant revision dependencies within your IT environment.
- HPE Firmware Update Implementation Service: Implementation of firmware updates for selected HPE server, storage, and solution products, taking into account the relevant revision dependencies within your IT environment.
- Implementation assistance services: Highly trained technical service specialists to assist you with a variety of activities, ranging from design, implementation, and platform deployment to consolidation, migration, project management, and onsite technical forums.
- HPE Service Credits: Access to prepaid services for flexibility to choose from a variety of specialized service activities, including assessments, performance maintenance reviews, firmware management, professional services, and operational best practices.

Notes: To review the list of Lifecycle Services available for your product go to:

<https://www.hpe.com/services/lifecycle>

For a list of the most frequently purchased services using service credits, see the [HPE Service Credits Menu](#)

Other Related Services from HPE Services:

HPE Education Services

Training and certification designed for IT and business professionals across all industries. Broad catalogue of course offerings to expand skills and proficiencies in topics ranging from cloud and cybersecurity to AI and DevOps. Create learning paths to expand proficiency in a specific subject. Schedule training in a way that works best for your business with flexible continuous learning options.

<https://www.hpe.com/services/training>

Service and Support

Defective Media Retention

An option available with HPE Complete Care Service and HPE Tech Care Service and applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

Consult your HPE Sales Representative or Authorized Channel Partner of choice for any additional questions and services options.

Parts and Materials

HPE will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

How to Purchase Services

Services are sold by Hewlett Packard Enterprise and Hewlett Packard Enterprise Authorized Service Partners:

- Services for customers purchasing from HPE or an enterprise reseller are quoted using HPE order configuration tools.
- Customers purchasing from a commercial reseller can find services at <https://ssc.hpe.com/portal/site/ssc/>

AI Powered and Digitally Enabled Support Experience

Achieve faster time to resolution with access to product-specific resources and expertise through a digital and data driven customer experience

Sign into the HPE Support Center experience, featuring streamlined self-serve case creation and management capabilities with inline knowledge recommendations. You will also find personalized task alerts and powerful troubleshooting support through an intelligent virtual agent with seamless transition when needed to a live support agent.

<https://support.hpe.com/hpesc/public/home/signin>

Service and Support

Consume IT On Your Terms

[HPE GreenLake](#) edge-to-cloud platform brings the cloud experience directly to your apps and data wherever they are—the edge, colocations, or your data center. It delivers cloud services for on-premises IT infrastructure specifically tailored to your most demanding workloads. With a pay-per-use, scalable, point-and-click self-service experience that is managed for you, HPE GreenLake edge-to-cloud platform accelerates digital transformation in a distributed, edge-to-cloud world.

- Get faster time to market
- Save on TCO, align costs to business
- Scale quickly, meet unpredictable demand
- Simplify IT operations across your data centers and clouds

To learn more about HPE Services, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized Channel Partner. Contact information for a representative in your area can be found at "Contact HPE" <https://www.hpe.com/us/en/contact-hpe.html>

For more information

<http://www.hpe.com/services>

Related Options

Extension Bars

HPE G2 IEC C20 Input/(8) C13 Expansion Outlets/PDU Extension Bar Kit P9Q66A

Notes: All kits include 2 extension bars with a locking C19 input power cord (1.8m).

IEC Locking Power Cords

HPE C13 - C14 WW 250V 10Amp 0.7m Black Locking Power Cord Q0P67A

HPE C13 - C14 WW 250V 10Amp 0.7m Black 6-pack Locking Power Cord Q0Q02A

HPE C13 - C14 WW 250V 10Amp 1.4m Black Locking Power Cord Q0P68A

HPE C13 - C14 WW 250V 10Amp 1.4m Black 6-pack Locking Power Cord Q0Q03A

HPE C13 - C14 WW 250V 10Amp 2m Black Locking Power Cord Q0P69A

HPE C13 - C14 WW 250V 10Amp 2m Black 6-pack Locking Power Cord Q0Q04A

HPE C13 - C14 WW 250V 10Amp 3m Black Locking Power Cord Q0P70A

HPE C19 - C20 WW 250V 16Amp 0.7m Black Locking Power Cord Q0R19A

HPE C19 - C20 WW 250V 16Amp 2m Black Locking Power Cord Q0P72A

HPE C19 - C20 WW 250V 16Amp 2m 6-pack Black Locking Power Cord Q0R17A

Notes: HPE Locking Power Cords are only supported on either C13/14 or C19/20 outlets using HPE G2 PDUs.

IEC Standard Power Cords

HPE C13 - C14 WW 250V 10Amp 1.4m Jumper Cord 142257-006

HPE C13 - C14 WW 250V 10Amp 2.0m Jumper Cord A0K02A

HPE C13 - C14 WW 250V 10Amp Flint Gray 2.0m Jumper Cord AF573A

HPE C13 - C14 WW 250V 10Amp 2.5m Jumper Cord 142257-002

HPE C13 - C14 WW 250V 10Amp 3.0m Jumper Cord 142257-003

HPE C20 - C13 WW 250V 15Amp 2.0m Jumper Cord AF590A

HPE C19 - C20 WW 250V 16Amp Flint Gray 1.20m Jumper Cord AF575A

HPE C19 - C20 WW 250V 16Amp Flint Gray 2.0m Jumper Cord AF574A

HPE C19 - C20 WW 250V 16Amp 2.5m Jumper Cord 295633-B22

Country-Specific Power Cords

HPE C13 - Nema 5-15P US/CA 110V 10Amp 1.83m Power Cord AF556A

HPE C13 - Nema 5-15P TH/PH 250V 10Amp 1.83m Power Cord AF559A

HPE C19 - CEE-VII EU 250V 16Amp 3.6m Power Cord AF576A

HPE C19 - Nema L6-20P NA/JP 250V 20Amp High Voltage 3.6m Power Cord AF593A

HPE Mounting Brackets

HPE Vertical PDU 10K G2 Mounting Kit H6L32A

Notes: This kit allows for vertical HPE G2 PDU models to be mounted in HPE 10000 G2 series racks and in the HPE Standard Series rack.

Related Options

Environmental Sensors

HPE G2 Metered PDUs include 2 physical sensor ports and can monitor and record up to eight sensor measurements. Data collected by each sensor can be viewed and managed through the integrated graphical user interface (GUI), or by third-party applications that communicate through SNMP or through a Redfish supported API. Consult the HPE G2 Metered PDU User Guide for more information on use with third-party software applications.

HPE G2 PDU Environmental Temperature Sensor P9T00A

Notes: Requires one input port and monitor/records one sensor measurement.

HPE G2 PDU Environmental Temperature and Humidity Sensor P9T01A

Notes: Requires one input port and monitors/records two sensor measurements.

HPE G2 PDU Environmental 3 Temperature and 1 Humidity Sensor P9T02A

Notes: Requires one input port and monitors/records four sensor measurements.

HPE G2 PDU Open Door Sensor P9T03A

Notes: Requires two input ports and monitors/records two sensor measurements.

HPE G2 PDU Leak Detection Sensor P9T04A

Notes: Requires one input port and monitors/records one sensor measurement. Kit covers up to six linear meters and can be expanded to cover up to thirty linear meters with the addition of up to four HPE G2 PDU Leak Detection Sensor Extension Kits (P9T08A).

HPE G2 PDU Sensor Port Hub P9T07A

Notes: This is an adapter that expands a single physical sensor port into three physical sensor ports.

HPE G2 PDU Leak Detection Sensor Extension Kit P9T08A

Notes: Leak Detection Sensor (P9T04A) must be purchased separately to use in conjunction with this kit. Up to four Extension Kits can be added to a single Leak Detection Sensor to cover up to a maximum of thirty linear meters.

Technical Specifications

Mounting options for Vertical PDU models in HPE Advanced and Enterprise racks (1075mm depth)							
Model	W x H x D (inches)	Unit Weight (lbs.)	Vertical Height	Maximum PDUs per Side of Rack			
				22U	36U	42U	48U
P9S15A	2.047 x 68.898 x 2.087	17.6	Full-Height	-	-	2	2
P9S18A	2.047 x 68.898 x 2.087	15.0	Full-Height	-	-	2	2
P9S19A	2.047 x 68.898 x 2.087	16.2	Full-Height	-	-	2	2
P9S20A	2.047 x 68.898 x 2.087	12.5	Full-Height	-	-	2	2
P9S21A	2.047 x 68.898 x 2.953	25.2	Full-Height	-	-	1	1
P9S22A	2.047 x 68.898 x 2.953	25.6	Full-Height	-	-	2	2
P9S23A*	2.047 x 71.654 x 4.409	32.0	Full-Height	-	-	2	2
P9S24A	2.047 x 68.898 x 2.953	20.2	Full-Height	-	-	2	2
P9S25A*	2.047 x 71.654 x 4.409	24.2	Full-Height	-	-	1	1

* HPE high density model mounts on its side with outlets facing the back of the rack

Notes: HPE G2 Advanced and Enterprise 1200mm deep racks include an extra set (2) of PDU trays in the rear of the rack enabling support of up to 2x the number of PDUs listed above for 1075mm deep racks.

Model Matrix – Input Power						
Model	Region	Phase & Nominal Voltage	Input Amps	Circuit Breaker	Input Plug Type	Input Cord Length
P9S15A	NA/JP	1-ph, 208V	24A	(2) 2-pole 20A	L6-30P	10'
P9S18A	INTL	1-ph, 230V	32A	(2) 1-pole 16A	IEC 32A, 1ph	10'
P9S19A	NA/JP	3-ph, 208V	24A	(3) 2-pole 20A	L15-30P	10'
P9S20A	INTL	3-ph, 200–240V 3-ph, 346–415V	16A	none	IEC 16A, 3ph	10'
P9S21A	NA/JP	3-ph, 208V	40A	(6) 2-pole 20A	CS8365C	10'
P9S22A	NA/JP	3-ph, 208V	48A	(6) 2-pole 20A	IEC 60A, 3ph	10'
P9S23A	NA/JP	3-ph, 208V	48A	(6) 2-pole 20A	IEC 60A, 3ph	10'
P9S24A	INTL	3-ph, 200–240V 3-ph, 346–415V	32A	(6) 1-pole 16A	IEC 32A, 3ph	10'
P9S25A	INTL	3-ph, 200–240V 3-ph, 346–415V	32A	(6) 1-pole 16A	IEC 32A, 3ph	10'

Notes: All Input Circuit Ratings for NA/JP models have been de-rated according to NEC requirements.

Nominal Input Voltage Ratings used for calculating output power are as follows:

- 200–208V: 208V
- 220–240V: 230V
- 200–240V/346–415V: 230V

Technical Specifications

Model Matrix – Output Power						
Model	Region	kVA	Output Voltage Range	Output Receptacles	Support Extension Bar Options	Support Locking Power Cord Options
P9S15A	NA/JP	4.9	200–208V	(20)C13, (4)C19	✓	✓
P9S18A	INTL	7.3	220–240V	(20)C13, (4)C19	✓	✓
P9S19A	NA/JP	8.6	200–208V	(18)C13, (6)C19	✓	✓
P9S20A	INTL	11	220–240V	(18)C13, (6)C19	✓	✓
P9S21A	NA/JP	14.4	200–208V	(12)C13, (12)C19	✓	✓
P9S22A	NA/JP	17.3	200–208V	(12)C13, (12)C19	✓	✓
P9S23A	NA/JP	17.3	200–208V	(36)C13, (12)C19	✓	✓
P9S24A	INTL	22	220–240V	(12)C13, (12)C19	✓	✓
P9S25A	INTL	22	220–240V	(36)C13, (12)C19	✓	✓

Technical Specifications

Voltage	Amps	# Wires	Plug Name	Sample Plug Image (color may vary by manufacturer)	
				Receptacle (R)	Plug (P)
100-125 V Single Phase	15 A	3	NEMA 5-15		
	20 A	3	NEMA 5-20		
	30 A	3	NEMA L5-30		
200-240 V Single Phase	20 A	3	IEC C20		
	30 A	3	NEMA L6-30		
	32 A	3	IEC 309 32A		
	50 A	3	CS8265C		
	63 A	3	IEC 309 63A		
200-208 V NA/JPN Three Phase	30 A	5	NEMA L15-30		
	30 A	5	NEMA L21-30		
	50 A	4	CS8365C		
	60 A	4	IEC 309 60A		
200-240 V 400-415 V INTL Three Phase	16 A	5	IEC 309 16 A		
	32 A	5	IEC 309 32 A		

Technical Specifications

Operating Temperature	50° to 140°F (10° to 60°C)
Operating Relative Humidity (%)	10% to 90%
Operating Elevation	0 to 10,000 ft. (0 to 3000 m)
Storage Temperature	-4° to 140°F (-20° to 60°C)
Storage Relative Humidity (%)	5% to 95%
Storage Elevation	0 to 30,000 ft. (0 to 9144 m)
Conformance Standards	UL or CSA, CB Test+ FCC, ICES, VCCI - NA/JPN models CE, DEMKO, EAC, KC+KCC, ACMA, Ukraine - INTL models UL or CSA, CB Test+CE, DEMKO, EAC, FCC, ICES, KCC, KC, VCCI ACMA, Ukraine - WW models
Kit Contents	All G2 Metered & Switched PDU models ship with: <ul style="list-style-type: none"> – Mounting brackets/hardware – Tie wraps – HPE IEC Locking Power Cord sample (for models with either C13 and/or C19 outlets) – Read me first card

Environment-friendly Products and Approach - End-of-life Management and Recycling

Hewlett Packard Enterprise offers end-of-life [product return, trade-in, and recycling programs](#), in many geographic areas, for our products. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE Directive (2012/19/EU) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the [Hewlett Packard Enterprise web site](#). These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.

Summary of Changes

Date	Version History	Action	Description of Change
16-Feb-2026	Version 7	Changed	New branding applied to document
04-Dec-2023	Version 6	Changed	Service and Support Section was updated
04-Oct-2021	Version 5	Changed	Service and Support Section was updated
01-Oct-2018	Version 4	Changed	Models and Related Options were updated.
02-Jul-2018	Version 3	Changed	Models section was updated
05-Mar-2018	Version 2	Changed	Related Options, Model Matrix sections were updated
27-Mar-2017	Version 1	Added	New QuickSpecs.

[Shape the Future of QuickSpecs - Your Input Matters](#)

[Chat now](#)

© Copyright 2026 Hewlett Packard Enterprise Development Company, L.P. The information contained herein is subject to change without notice.

The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

a00002910enw - 15865 - Worldwide - V7 - 16-February-2026
HEWLETT PACKARD ENTERPRISE
HPE.com

