



Release Notes:

Version J.02.02A Software

for the ProCurve Secure Routers 7000dl Series

Release J.02.02A supports these routers:

- ProCurve Secure Router 7102dl (J8752A)
- ProCurve Secure Router 7203dl (J8753A)

These release notes include information on the following:

- Downloading switch software and Documentation from the Web ([page 1](#))
 - Clarification of operating details for certain software features ([page 5](#))
 - Software features available in release J.02.02A ([page 5](#))
 - A listing of software fixes included in release J.02.02A ([page 7](#))
-

Boot ROM Update Required for J.02.02A

A successful update to J.02.02A from any previous J.0x.xx software version requires updating the Secure Router 7000dl with the current Boot ROM version, J.02.02A. If your router is currently running a pre-J.02.02A software version, you must update the Boot ROM before installing the J.02.02A software. This Boot ROM update is required for J.02.02A software to support additional product capabilities, for example, the use of compact flash. The J02.02 Boot ROM image is installed in a separate operation, before loading the J.02.02A software. See [page 2](#) for more information.

© Copyright 2005 Hewlett-Packard Company, LP. The information contained herein is subject to change without notice.

Publication Number

Part Number 5991-2124
July 2005

Applicable Product

ProCurve Secure Router 7102dl	(J8752A)
ProCurve Secure Router 7203dl	(J8753A)

Trademark Credits

Microsoft®, Windows®, and Windows NT® are US registered trademarks of Microsoft Corporation. Adobe® and Acrobat® are trademarks of Adobe Systems Incorporated. Java™ is a US trademark of Sun Microsystems, Inc.

Disclaimer

HEWLETT-PACKARD COMPANY MAKES NO WARRANTY OF ANY KIND WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Hewlett-Packard shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Hewlett-Packard assumes no responsibility for the use or reliability of its software on equipment that is not furnished by Hewlett-Packard.

Warranty

See the Customer Support/Warranty booklet included with the product.

A copy of the specific warranty terms applicable to your Hewlett-Packard products and replacement parts can be obtained from your HP Sales and Service Office or authorized dealer.

Hewlett-Packard Company
8000 Foothills Boulevard, m/s 5551
Roseville, California 95747-5551
<http://www.procurve.com>

Contents

Software Management

Software Updates	1
Downloading Documentation and Software from the Web	1
Downloading Software to the Router	2
Saving Configurations While Using the CLI	2
Saving the Current Configuration as the Start-Up Configuration	3
Saving the Current or Start-Up Configuration to Compact Flash	3
Saving the Current or Start-Up Configuration to a TFTP Server	3
ProCurve Switch, Routing Switch, and Router Software Keys	4
Minimum Software Versions for Secure Router 7000dl Modules	4

Enhancements

Release J.02.02A Enhancements	5
System-Level Enhancement: Default Boot Path Changed	5
What has changed?	5
Why make this change?	6
Updating Existing Routers to Boot From Compact Flash	6
Release J.02.01 Enhancements	7

Software Fixes

Release J.02.02A	8
Release J.02.01	9

Known Software Issues and Limitations

Release J.02.02A	10
------------------------	----

— *This page is intentionally unused.* —

Software Management

Software Updates

Check the ProCurve Networking Web site frequently for software updates for the various ProCurve products you may have in your network.


Downloading Documentation and Software from the Web

You can download software updates and the corresponding product documentation from ProCurve Networking's Web site as described below.

To Download a Software Version:

1. Go to the ProCurve Networking Web site at:
<http://www.procurve.com>.
2. Click on **Software updates** (in the sidebar).
3. Under **Latest software**, click on **Secure Router 7000dl Series**.

To Download Product Documentation: You will need the Adobe® Acrobat® Reader to view, print, and/or copy the product documentation.

1. Go to ProCurve Networking's Web site at <http://www.procurve.com>.
2. Click on **Technical support**, then **Product manuals**.
3. Click on the name of the product for which you want documentation.
4. On the resulting Web page, double-click on a document you want.
5. When the document file opens, click on the disk icon  in the Acrobat® toolbar and save a copy of the file.

Downloading Software to the Router

Caution

The startup-config file generated by the latest software release is compatible with the same file generated by earlier software releases. HP recommends that you backup your current configuration to compact flash or a TFTP server before performing any software update. See “[Saving the Current or Start-Up Configuration to Compact Flash](#)” or “[Saving the Current or Start-Up Configuration to a TFTP Server](#)”.

ProCurve Networking periodically provides software updates through the ProCurve Networking Web site (<http://www.procurve.com>). After you acquire the new software file, use the ProCurve Secure Router GUI, TFTP, XModem, FTP, or compact flash to update the router software. See the *Upgrading SROS Software Configuration Guide* (5991-2123) for instructions and more information.

Notes

Downloading new software does not change the current router configuration. The router configuration is contained in a separate file that can also be transferred, for example, for archive purposes or to be used in another router of the same model.

Saving Configurations While Using the CLI

The router operates with two configuration files:

- **Running-Config File:** Exists in volatile memory and controls router operation. Rebooting the router erases the current running-config file and replaces it with an exact copy of the current startup-config file. To save a configuration change, you must save the current configuration in the running-config file to the startup-config file.
- **Startup-Config File:** Exists in flash (non-volatile) memory and preserves the most recently-saved configuration as the “permanent” configuration. When the router reboots for any reason, an exact copy of the current startup-config file becomes the new running-config file in volatile memory.

You may use the **write memory** command to save changes made to the running-config file to the startup-up config file. Also, the system prompts you to save any unsaved changes when you leave the configuration level.

Saving the Current Configuration as the Start-Up Configuration

When you use the CLI to make a configuration change, the router places the change in the running-config file. If you want to preserve the change across reboots, you must save the change to the startup-config file. Otherwise, the next time the router reboots, the change will be lost.

To save configuration changes while using the CLI:

1. From the Enable prompt enter:
#copy running-config startup-config
2. Verify that the Configuration built message displays, indicating that the download is complete. The current configuration is now saved as the startup configuration file, and the router will execute the file at each power-up.

The current configuration in the running-config file also may be saved to compact flash or a TFTP server as a **.txt** file (to allow it to be opened in a text editor). You also may use the **write memory** command in place of the above steps.

Saving the Current or Start-Up Configuration to Compact Flash

1. To save a configuration file to compact flash, from the Enable prompt enter:
#copy <config-file> cflash <filename>
where **<config-file>** is either **running-config** or **startup-config** and **<filename>** is a name that you choose, ending in **.txt**.
2. Verify that the Percent Complete 100% message displays, indicating that the download is complete. The current configuration is now saved in compact flash with the specified filename.

Saving the Current or Start-Up Configuration to a TFTP Server

1. To initiate a download of a configuration file to an external TFTP server, from the Enable prompt enter:
#copy <config-file> tftp
where **<config-file>** is either **running-config** or **startup-config**.
2. Enter the IP address of the TFTP server when prompted for the Address of remote host.
3. Enter a filename ending in **.txt** for the saved configuration when prompted for the Destination filename.

All configuration files downloaded from the router should have a **.txt** extension. Use identifiable names when saving the configuration, such as the date, for example, **042504.txt**.

ProCurve Switch, Routing Switch, and Router Software Keys

Software Letter	ProCurve Switch, Routing Switch, or Router
C	1600M, 2400M, 2424M, 4000M, and 8000M
E	Switch 5300xl Series (5304xl, 5308xl, 5348xl, and 5372xl)
F	Switch 2500 Series (2512 and 2524), Switch 2312, and Switch 2324
G	Switch 4100GL Series (4104GL, 4108GL, and 4148GL)
H	Switch 2600 Series, Switch 2600-PWR Series <ul style="list-style-type: none"> • H.07.50 and Earlier • H.08.55 and Greater
H	Switch 6108: H.07.xx and Earlier
I	Switch 2800 Series (2824 and 2848)
J	Secure Router 7000dl Series (7102dl and 7203dl)
M	Switch 3400cl Series (3400-24G and 3400-48G) and Series 6400cl (CX4 6400cl-6XG and X2 6400cl-6XG)
N/A	Switch 9300 Series (9304M, 9308M, and 9315M), Switch 6208M-SX and Switch 6308M-SX (Uses software version number only; no alphabetic prefix. For example 07.6.04.)

Minimum Software Versions for Secure Router 7000dl Modules

ProCurve Secure Router Module	Minimum Supported Software Version
J8451A ProCurve Secure Router 1xT1 Interface Module	J.01.02B
J8452A ProCurve Secure Router 1xT1 + DSX-1 Interface Module	J.01.02B
J8453A ProCurve Secure Router 2xT1 Interface Module	J.01.02B
J8454A ProCurve Secure Router 1xE1 Interface Module	J.01.02B
J8455A ProCurve Secure Router 1xE1 + G.703 Interface Module	J.01.02B
J8456A ProCurve Secure Router 2xE1 Interface Module	J.01.02B
J8458A ProCurve Secure Router 1xSerial Interface Module	J.01.02B
J8459A ProCurve Secure Router 1xADSL2+ Annex A Interface Module	J.01.02B
J8759A ProCurve Secure Router 1xADSL2+ Annex B Interface Module	J.02.01A
J8460A ProCurve Secure Router ISDN BRI U Backup Module	J.01.02B

ProCurve Secure Router Module	Minimum Supported Software Version
J8461A ProCurve Secure Router ISDN BRI S/T Backup Module	J.01.02B
J8462A ProCurve Secure Router Analog Modem Backup Module	J.01.02B
J8463A ProCurve Secure Router 8xT1/E1 Wide Module	J.01.02B
J8471A ProCurve Secure Router 7100/7200 IPSec Module	J.01.02B

Enhancements

Unless otherwise noted, each new release includes the features added in all previous releases.

Release J.02.02A Enhancements

System-Level Enhancement: Default Boot Path Changed

Concurrent with the release of J.02.02A software, ProCurve has changed the default boot path in the ProCurve Secure Router products it builds. Products with the following serial numbers, or later, use compact flash as the primary (default) boot path for the router software and router configuration files.

Table 1. ProCurve Secure Router Serial Numbers That Boot From Compact Flash

Product	Serial Number
ProCurve Secure Router 7102dl (J8752A)	US525TRAP4 or later.
ProCurve Secure Router 7203dl (J8753A)	US522TS252 or later.

The secondary boot path is the router's internal flash memory. Prior to this change, the 7102dl and 7203dl products booted by default from the files installed on internal flash at manufacturing time.

What has changed?

At manufacturing time, two software files are loaded into internal flash: the most recent software and an exact copy of that software, renamed to `SROS.BIZ`.

The default boot path for the software and configuration files is set as follows:

```
boot system cflash SROS.BIZ flash SROS.BIZ
boot config cflash startup-config flash startup-config
```

By default, the router tries to boot a file named `SROS.BIZ` from compact flash. If this file or compact flash is not present, the router boots `SROS.BIZ` from internal flash. In addition, by default, the router tries to use a configuration file named `startup-config` from compact flash. If this file or compact flash is not found, the router uses `startup-config` from internal flash.

Why make this change?

For ease of router deployment. A network administrator can now pre-configure a router using compact flash, without ever physically touching the router. All that is required is a PC equipped with a compact flash reader/writer. First, build a valid `startup-config` file and copy it to compact flash. Next, rename the current software file to `SROS.BIZ` and copy it to compact flash. With these two files loaded on compact flash, a network administrator can drop-ship the compact flash and a router to a remote site. At the remote site, someone inserts the compact flash into the router and attaches the network cables. When finished, the power cord is attached and plugged into a suitable power outlet, powering up the router. The router, by default, uses the software file (`SROS.BIZ`) and configuration file (`startup-config`) on the supplied compact flash to boot the system.

Note

Only routers built with serial numbers in Table 1 on page 5 boot by default from compact flash. Routers with earlier serial numbers can be updated to use compact flash by default. See [“Updating Existing Routers to Boot From Compact Flash” on page 6](#) for the update instructions.

Updating Existing Routers to Boot From Compact Flash

ProCurve Secure Routers with serial numbers below those in Table 1 on page 5 can be manually configured to use the new default boot path from compact flash. Follow the steps below.

1. Update the router Boot ROM to version J.02.02A.
2. Load and boot from software version J.02.02A.
3. Make any necessary changes to the router's configuration and save the running-config file. You now have a current `startup-config` file in flash.

```
ProCurveSR7203dl>  
ProCurveSR7203dl>enable  
ProCurveSR7203dl#write memory
```

4. Rename the current software file to `SROS.BIZ`. The file name must be in all capital letters.

```
ProCurveSR7203dl#copy flash J02_02A.biz flash SROS.BIZ
```

5. If you are using compact flash, copy the `SROS.BIZ` file and the `startup-config` file to compact flash. If you are not using compact flash, go to [step 6](#).

```
ProCurveSR7203dl#copy running-config cflash startup-config
ProCurveSR7203dl#copy flash J02_02A.biz cflash SROS.BIZ
```

6. Change the primary boot path to compact flash and the backup to internal flash.

```
ProCurveSR7203dl#conf term
ProCurveSR7203dl(config)# boot system cflash SROS.BIZ flash SROS.BIZ
ProCurveSR7203dl(config)# boot config cflash startup-config flash startup-config
```

Release J.02.01 Enhancements

The following enhancements are described in the guides referenced in each enhancement overview. For the latest version of any of these guides, refer to [“Downloading Documentation and Software from the Web” on page 1](#).

Summary of J.02.01 Enhancements Software Fixes

J.02.01 Enhancement	Overview
Compact Flash Support	<p>Added capability to copy boot image directly from compact flash to boot sector.</p> <p>Added capability to format compact flash with SROS running.</p> <p>Added capability to boot from a specific file from compact flash.</p> <p>For more information, see boot config and boot system the section titled “Global Configuration Mode Command Set” in the <i>SROS Command Line Interface Reference Guide</i> (April 2005 edition or later).</p>
ADSL Annex B module	Added software support for ADSL Annex B module.
RFC1483 on ADSL/ATM link	Added support for RFC1483 on ADSL/ATM link.
GRE (IP Only)	<p>The current implementation supports IP protocol only.</p> <p>For more information on GRE commands, see the section titled “Tunnel Configuration Command Set” in the <i>SROS Command Line Interface Reference Guide</i> (April 2005 edition or later).</p>
HDLC (Cisco)	<p>HDLC is a protocol developed by the International Organization for Standardization (ISO). It is used throughout the world and widely implemented because it supports both half duplex and full duplex communication lines, point to point, and multi-point networks, on both switched or non-switched links. HDLC is designed to permit synchronous, protocol transparent data transmission. HDLC also has many off shoots. Some of these are Synchronous Data Link Control (SDLC) and Link Access Procedure-Balanced (LAP-B), and PPP</p> <p>For more information on HDLC commands, see the section titled “HDLC Command Set” in the <i>SROS Command Line Interface Reference Guide</i> (April 2005 edition or later).</p>

J.02.01 Enhancement	Overview
Multi-Link Frame-Relay support	<p>Multilink Frame Relay (MFR) for the User-to-Network Interface (UNI) and the Network-to-Network Interface (NNI) provides physical interface emulation for frame relay devices. The emulated physical interface consists of one or more physical links, called “bundle links”, aggregated together into a single “bundle” of bandwidth. This service provides a frame-based inverse multiplexing function, sometimes referred to as an “IMUX”.</p> <p>The bundle provides the same order-preserving service as a physical layer for frames sent on a data link connection. In addition, the bundle provides support for all Frame Relay services based on UNI and NNI standards.</p> <p>For more information, see the <i>8xT1/E1 Wide Module) Quick Configuration Guide</i>. Also, see pages 581 and 582 in the section titled “Frame Relay Interface Config Command Set” in the <i>SRoS Command Line Interface Reference Guide</i> (April 2005 edition).</p>
SNMP Views	<p>Added SNMP Views. For more information, see the snmp-server view command in the section titled “Global Configuration Mode Command Set” in the <i>SRoS Command Line Interface Reference Guide</i> (April 2005 edition or later).</p>
802.1X supplicant mode	<p>Added 802.1X supplicant mode. For more information, see the port-auth supplicant enable command in the section titled “Ethernet Interface Configuration Command Set” in the <i>SRoS Command Line Interface Reference Guide</i> (April 2005 edition or later).</p>
SIP-ALG	<p>Improved the performance through the router.</p>

Software Fixes

Release J.01.02B was the first software release for the ProCurve Secure Router 7000dl Series.

Release J.02.02A

Problems Resolved in Release J.02.02A

- **(none)** — Added capability of configuring the Bundle ID for an MFR bundle.
- **28428** — Allow setting the path to the software image (operating system) to a file that does not exist.
- **28183** — Changed rate-limiting algorithm to prevent a huge burst of traffic after periods of inactivity.
- **28429** — Changed **wr mem** to write to either primary or secondary configuration file, depending on boot settings.
- **28567** — Changed **FIN** timeout in firewall.
- **26893** — Fixed issue where over 73K TCP firewall sessions were causing reboots.
- **27014** — Fixed issue where deleting a bridge could cause sluggish performance.
- **27088** — Fixed issue where the incorrect VPN Mode-Config address was displayed.

- **27124** — Fixed issue where the Media Type in SDP of the SIP Invite message was getting modified with random numbers.
- **27281** — Fixed issue where DHCP relay was not working across VLANs.
- **27315** — Fixed issue where the unit would reboot when the command show run was entered if the configuration contained DHCP server pool options.
- **27324** — Fixed issue where the bandwidth command for a GRE tunnel interface was not being displayed in the **show run** output and was not getting saved to the startup script.
- **27352** — Fixed problem with incorrect NTP server in running config.
- **27372** — Fixed issue where a TDM group could not be assigned to a Dual E1 module.
- **27407** — Fixed issue on the 7203/7102 where runt ARP packets were being sent by the unit.
- **28957** — Fixed connection / binding problem with HDLC and Serial interface.
- **27964** — IPCP will not negotiate to Juniper router. The symptom would be non-interoperability with Multilink PPP.
- **28373** — Protocol stack enhancements.
- **27573** — SNMP OID cleanup.

Release J.02.01

Problems Resolved in Release J.02.01

- Fixed buffer overflow in https server that caused a reboot.
- Fixed OSPF not observing path-type when doing route selection.
- Fixed minor issues related to compact flash.
- Fixed a default configuration issue that occurred with ADSL/PPPoE overwriting the default route.
- Fixed E1+G.703 **ts16**, once configured, does not show in **show config** output.
- Fixed **terminal line length**, once set to zero, cannot be set to anything else again.
- WFQ in WEB changed to be enabled by default

Known Software Issues and Limitations

This section identifies issues you may encounter when using a ProCurve Secure Router 7000dl.

Release J.02.02A

- **29068** — Cannot create secondary address on 802.1Q interfaces.
- **28759** — Web GUI - "**Telnet/SSH/Console -> Use password.**" SSH does not use the specified password.
- **27370** — Files that are eight characters or less combined with file extensions of three characters or less cause the file to be displayed in all caps on the router. For example, abcdefgh.biz would be displayed in all caps on the router.
- **27511** — The **test-pattern insert** and **show test-pattern** should not be allowed with 1's and 0's pattern.
- **27626** — **no debug ip ospf hello** Command not available.
- **27827** — **Show int adsl 1/1 ver** and **show int adsl 1/1 info** commands do not display information correctly.
- **26606** — Debug commands for HDLC do not work.
- **26620** — DHCP Client does not work on an HDLC interface. This feature was not implemented for HDLC.

— *This page is intentionally unused.* —



© 2005 Hewlett-Packard Development
Company, LP. The information contained
herein is subject to change without notice.

Part Number 5991-2124
July 2005