

Aruba 2930M 24 HPE Smart Rate PoE+ 1-slot Switch (JL324A)



What's new

- Aruba Layer 3 switch series that is easy to deploy and manage with Aruba ClearPass Policy Manager and on-premise with Aruba Airwave.
- Simplify with Zero Touch Provisioning and cloud-based Aruba Central support.
- Scale with modular 10 chassis stacking and up to 1440W PoE.
- Modular 10GbE and 40GbE uplinks and HPE Smart Rate multi-gigabit support.
- Models with 24 ports of HPE Smart Rate with IEEE 802.3bz.
- High Power PoE models deliver up to 60W of PoE per port.

Overview

The Aruba 2930M Switch Series is designed for digital workplaces optimized for mobile users. These powerful Layer 3 access switches are easy to deploy and manage with advanced security and network management tools like Aruba ClearPass Policy Manager, Aruba AirWave and cloud-based Aruba Central. Modular stacking, uplinks and power provide scalability and simplicity for enterprise edge, SMB and branch office networks. The 2930M delivers performance and value with support for static, RIP and Access OSPF routing, 10GbE and 40GbE uplinks, models with 24 ports of HPE Smart Rate multi-gigabit Ethernet, up to 1440W of PoE, robust QoS, and Dynamic Segmentation for unified and secure access.

Features

High-Performance Layer 3 Access Switches

The Aruba 2930M Switch Series provides performance, security, and ease of use for enterprise edge, SMB, and branch office networks.

Optimized for the digital workplace with unified management tools such as Aruba ClearPass Policy Manager, Aruba Airwave and Aruba Central. Provides optimal configuration automatically when connected to Aruba access points for PoE priority, VLAN configuration, and rogue AP containment.

Pay as you grow modular stacking (10 chassis) and modular 10GbE (SFP+) and 40GbE (QSFP+) uplinks. HPE Smart Rate multi-gigabit Ethernet models support high speed APs over existing cabling and upgradeable power supplies allow your network to quickly scale when more PoE is needed.

Robust Layer 3 feature set includes Access OSPF, static and RIP routing, ACLs, Dynamic Segmentation, sFlow, IPv6 with no software licensing required.

Designed with a power ProVision ASIC, the 2930M supports multiple programmatic interfaces, including REST APIs and Openflow 1.0 and 1.3, to enable automation of network operations, monitoring, and troubleshooting.

Performance and Power at the Edge

The Aruba 2930M Switch Series is designed with a powerful Aruba ProVision ASIC, to enable the mobile campus with low latency, increased packet buffering, and adaptive power consumption.

Increase performance with selectable queue configurations and associated memory buffering that meets your specific network application requirements.

Plug and play with up to 10 chassis stacking allowing automated failover enhances network resiliency and RPS support delivers power redundancy.

Supports hot swappable and redundant PoE power for wireless access points, cameras and phones and can easily scale to 1440W with choice of power supplies. High power PoE models deliver up to 60W of PoE per port.

Security and Quality of Service You Can Rely On

The Aruba 2930M Switch Series includes security and quality of services (QoS) features to build a network that meets ever-changing corporate policies and compliances while protecting your data from both inside and outside attacks.

Flexible authentication options include standards based security protocols such as 802.1X, MAC and Web Authentication, to enhance security and policy-driven application authentication.

Powerful multilevel-access security controls include source-port filtering, RADIUS/TACACS+, SSL, port security, and MAC address lockout.

Dynamic Segmentation provides user and port-based traffic tunneling to an Aruba Mobility Controller or Branch Gateway so that policies can be applied, advanced services can be extended to users and IoT devices, and traffic can be encrypted to protect the network.

Simplify with Integrated Wired/Wireless Management

The Aruba 2930M Switch Series supports Aruba ClearPass Policy Manager for unified and consistent policy between wired and wireless users and simplifies implementation and management of guest login, user onboarding, network access, security, QoS, and other network policies.

Aruba Airwave Network Management software provides an on-premise network management platform for wired and wireless network devices. Cloud-based management with Zero Touch Provisioning supported by Aruba Central.

Supports both cloud-based Central and on-premise AirWave with the same hardware ensuring change of management platform without ripping and replacing switching infrastructure.

RMON and sFlow provide advanced monitoring and reporting capabilities for statistics, history, alarms and events.

Out-of-band Ethernet management port keeps management traffic segmented from your network data traffic.

Technical specifications

Aruba 2930M 24 HPE Smart Rate PoE+ 1-slot Switch


Product Number	JL324A
Differentiator	Powerful and flexible high density 1U 24-port PoE+ access switch packed with HPE Smart Rate PoE+ ports ideal for advanced Wi-Fi deployments. This model has 24x 802.3bz 1/2.5/5GBase-T copper PoE+ ports. This model does support PoE/PoE+ with a Power over Ethernet budget of up to 860 Watts based on selected power supplies. Can take up to two power supplies power supplies ordered separately.
Ports	(24) RJ-45 autosensing 1/2.5/5GBASE-T PoE+ ports (1) Uplink module slot, (1) stacking module slot
Memory and processor	Dual Core ARM Coretex A9 @ 1016 MHz 1 GB DDR3 SDRAM Packet buffer size: 12.38 MB and 4.5MB Ingress, 7.785 Egress 4 GB eMMC
Latency	1000 Mb Latency: < 3.1 μ s 10 Gbps Latency: < 3.4 μ s
Throughput	up to 112 Mpps
Switching capacity	320 Gbps
PoE capability	Up to 840 Watts
Management features	Aruba AirWave Network Management Aruba Central IMC - Intelligent Management Center Command-line interface Web browser Configuration menu SNMP manager Telnet RMON1 FTP Out-of-band management (serial RS-232C or micro USB)
Power supply name	JL086A Aruba X372 54VDC 680W 100-240VAC Power Supply, JL087A Aruba X372 54VDC 1050W 110-240VAC Power Supply
Input voltage	100 - 127 / 200 - 240 VAC, rated or 110-127 / 200-240VAC, Rated depending on power supply
Operating humidity range	15 to 95% @ 104°F (40°C) (noncondensing up to 10000 ft)
Power consumption	2 power supplies are supported: JL086A PSU (each): 513W JL087A PSU (each): 873W
Heat dissipation	150 BTU/hr 162 kJ/hr
Product dimensions (metric)	4.39 x 44.25 x 32.43 cm
Weight	4.50 kg

For additional technical information, available models and options, please reference the QuickSpecs

HPE Aruba Networking Services

HPE Aruba Networking services simplify and accelerate the network technology lifecycle, enabling your network to scale with better predictability and cost-effectiveness. Whether you operate your own network and need to improve your IT efficiencies, or you want to offload some of the burden, we have the services you need to reach your goals.

Learn more about what HPE Services - Aruba Networking has to offer at: arubanetworks.com/services/



Support Services from HPE Aruba Networking

Our support portfolio provides the essential support elements as well as proactive and preventive features to help you improve your team's productivity and get the most from your network. Our support customers benefit from faster issue resolution, simplified operations and efficiencies, and reduced network issues.

Professional Services from HPE Aruba Networking

With deep intellectual capital and purpose-built tools, our team delivers a range of standard and custom professional services designed to accelerate your value from HPE Aruba Networking technology.

Project based services

include:

- Planning, audit, and assessment
- Architecture review and design
- Deployment, migration, and knowledge transfer

Annual subscription services include:

- Network optimization
- Intelligent Operations
- Customer Experience Management

Make the right purchase decision. Contact our presales specialists.

[Find a partner](#)



Chat now (sales)



Call now



Buy now



Share now



Get updates

Our [Education Services](#) allow your team to come up to speed quickly.

HPE Aruba Networking Network as-a-Service (NaaS)

Our NaaS solution, HPE Aruba Networking Managed Connectivity Services, part of the HPE GreenLake services family, simplifies network operations, accelerates equipment handling, and increases the value of your HPE Aruba Networking network. If you need expert guidance and automation-based operations for your team, please explore the NaaS approach from HPE Aruba Networking [here](#).

© Copyright 2023 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Image may differ from the actual product PSN1010256124BEEN, December, 2023.