

# HPE Aruba Networking 760 Series Hardened Access Points



## What's new

- High performance hardened Wi-Fi 7 access points with purpose-built models for industrial indoors, outdoors, large public venues, and hazardous environments
- AI-driven orchestration and management with HPE Aruba Networking Central helps provide amazing wireless experiences and operational efficiency
- It delivers up to 4.3 Gbps maximum 5 GHz + 6 GHz aggregate data rate, using dual 2x2 MIMO radios (5 GHz and 6 GHz 2x2), or up to 5.8 Gbps (in

## Overview

The HPE Aruba Networking 760 Series Hardened Access Points bring high performance WiFi 7 to challenging locations such as industrial sites, warehouses, and large public venues. These compact Wi-Fi 7 access points boost security, support Internet of Things (IoT) devices, and help provide accurate location services. HPE Aruba Networking Central helps drive efficient operations and provides AI-automation and machine learning (ML) insights for fine-tuned wireless connectivity.

With integrated IoT radios, fast 5GbE wired connectivity, and a limited lifetime warranty, the 760 series is purposebuilt to deliver high-performance WiFi 7 across a range of environmental conditions: indoor industrial, outdoors, and hazardous environments, delivering up to 5.8 Gbps maximum aggregate data rates using 6 GHz (4x4).

6 GHz 4x4)

- Industrial IoTready platform with highpower integrated Bluetooth and 802.15.4/Zigbee radios
- Low power indoor (LPI) power and standard power (SP) device operation, where available. Embedded GPS receiver for location and SP support
- Dynamic power save mode helps reduce energy consumption

For extreme environments, the 760EX models are hazardous location compliant, ideal for environments such as oil rigs, industrial manufacturing, and transportation sites.

## Features

### Hardened and Outdoor Wi-Fi 7

The HPE Aruba Networking 760 Series Hardened Access Points take advantage of the increased capacity of the 6 GHz band to deliver high speeds, wider channels for multi-gigabit traffic, and less interference in environments where typical indoor access points can't operate.

These small form factor APs have a built-in GPS receiver for standard power (SP) support and to help provide precision location services with FTM 802.11az capability.

Intelligent automation, AI insights, and unified infrastructure management, provided by HPE Aruba Networking Central, enhance wireless performance and help drive more efficient IT operations.

Dual radio, tri-band coverage across 2.4 GHz, 5 GHz, and 6 GHz delivers up to 4.3 Gbps maximum 5 GHz + 6 GHz aggregate data rate, using dual 2x2 MIMO radios (5 GHz and 6 GHz 2x2), or up to 5.8 Gbps (6 GHz 4x4). Supports up to 160 MHz wide channels.

Innovative dynamic antennas (integrated omni and directional, software provisioned) help customize the deployment to best suit a variety of different spaces (internal antenna models only, not supported on AP-764 model).

### Purpose-built Models Address Tough Environments

The HPE Aruba Networking 760 Series Hardened Access Points includes three small form factor models that each include a built-in GPS receiver for SP support and for providing precision location services with FTM 802.11az capability.

Designed for industrial indoor, outdoor environments, large public venues, and hazardous environments, the 760 series operates as low power indoor (LPI) and standard power (SP) devices where available.

The AP763 indoor model operates as an indoor LPI/SP (composite) device and is ideal for indoor warehouses, LPVs, industrial facilities, and indoor enterprise, where directional LPI is required (IP50 rating).

The AP764 hardened model operates as an outdoor SP device and is ideal for industrial enclosures, LPV enclosures and potential mesh, and supports external antennas for connectorized requirements (IP66/67 rating).

The AP765 outdoor model operates as an outdoor SP and is ideal for outdoor WiFi 7 coverage, indoor or outdoor warehouses, LPV, and industrial facilities (IP66/IP 67 rating). The AP765EX hazardous locations is Class 1 Division 2 and ATEX Zone 2 certified for HazLoc applications.

### Comprehensive Security Built-in

The HPE Aruba Networking 760 Series Hardened Access Points offer enhanced security with dynamic segmentation to mitigate the time-consuming and error-prone task of managing complex and static VLANs, ACLs, and subnets by dynamically assigning policies and keeping traffic secure and separated.

Network protection with stronger encryption and authentication with WPA3, secure credentials/keys storage for guest access with Enhanced Open, and user and IoT access policy enforcement firewalls.

AI-powered classification of all Wi-Fi clients and IoT devices through HPE Aruba Networking Central uses deep packet inspection to provide behavioral context that helps ensure devices are receiving proper policy enforcement and continuous monitoring.

To simplify policy enforcement, the HPE Aruba Networking 760 Series Hardened Access Points use the policy enforcement firewall (PEF) to encapsulate all traffic from the access point to the gateway (or mobility controller) for end-to-end encryption and inspection.

For enhanced device assurance, the 760 series APs include a built-in trusted platform module (TPM) for secure storage of credentials, keys, and boot code.

### **Industrial IoT Ready Platform**

The HPE Aruba Networking 760 Series Hardened Access Points can serve as flexible IoT platforms that bolster network security and provide coverage for a broad range of IoT devices without the need for network overlays for IoT devices.

Seamlessly onboard IoT devices with highpower Bluetooth and 802.15.4/Zigbee radios that help simplify deploying and managing IoT devices. USB port supports additional connectivity to a broad range of IoT devices.

HPE Aruba Networking Central IoT operations unify visibility of IT and OT infrastructure within the network health dashboard by extending network monitoring, visibility, and insights to BLE, Zigbee, and other non-IP IoT devices.

The 760 series can run IoT containerized applications from the application store within HPE Aruba Networking Central to move processing to the edge, making it ideal for realtime AI inference.

A broad ecosystem of technology partners and certified solutions helps extend IoT capabilities and provide interoperability for easier installations and operations.

Technical specifications	HPE Aruba Networking 760 Series Hardened Access Points
<b>Deployment</b>	Hardened Outdoor Industrial Ruggedized Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, tri-band coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	HPE Aruba Networking 760 Series Outdoor Access Points models: AP-763/AP-765: Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional) AP-764: Outdoor IP-rated RP-SMA connectors
<b>Ultra tri-band (UTB) filtering</b>	No
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor
<b>Location services</b>	802.11 FTM support Built-in GPS GNSS receiver
<b>Cellular support</b>	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud Virtual Private Cloud (VPC) as a Service On-premises

**Certifications**

Wi-Fi Alliance®:  
 Wi-Fi CERTIFIED® a, b, g, n, ac, 6, 7  
 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE)  
 WMM, WMM PS, Wi-Fi agile multiband  
 Bluetooth SIG  
 Ethernet Alliance (E0, PoE PD Device Class 6)

**Regulatory**

FCC/ISED  
 CE marked  
 EU RED with NB TA (as needed)  
 ETSI EN 300328 2.4GHz  
 ETSI EN 301893 5GHz  
 ETSI EN 303687 (6GHz)  
 EN301489-1 / 489-17  
 EN 300440  
 EN 303413 GNSS (GPS)  
 IEC/EN 62368-1  
 EN 60601-1-1, EN60601-1-2

**Warranty**

Limited lifetime warranty. See the [warranty duration](#).

**Ports**

1 x 5GbE  
 USB 2.0  
 Reset button  
 Serial console

## SKU comparison

	HPE Aruba Networking AP-763 (EG) Flex Radio 2x2 Wi-Fi 7 Dynamic Omnidirectional Indoor AP (S4K13A)	HPE Aruba Networking AP-763 (EGF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omnidirectional TAA Indoor AP (S4K18A)	HPE Aruba Networking AP-763 (ID) Flex Radio 2x2 Wi-Fi 7 Dynamic Omnidirectional Indoor Access Point (S6A19A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.

	HPE Aruba Networking AP-763 (EG) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Indoor AP (S4K13A)	HPE Aruba Networking AP-763 (EGF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Indoor AP (S4K18A)	HPE Aruba Networking AP-763 (ID) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Indoor Access Point (S6A19A)
<b>Ultra tri-band (UTB) filtering</b>	No	No	No
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-763 (IL) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Indoor AP (S4K12A)	HPE Aruba Networking AP-763 (ILF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Indoor AP (S4K17A)	HPE Aruba Networking AP-763 (JP) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Indoor AP (S4K11A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.
<b>Ultra tri-band (UTB) filtering</b>	No	No	No

	HPE Aruba Networking AP-763 (IL) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Indoor AP (S4K12A)	HPE Aruba Networking AP-763 (ILF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Indoor AP (S4K17A)	HPE Aruba Networking AP-763 (JP) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Indoor AP (S4K11A)
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-763 (JPF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Indoor AP (S4K16A)	HPE Aruba Networking AP-763 (RW) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Indoor AP (S4K10A)	HPE Aruba Networking AP-763 (RWF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Indoor AP (S4K15A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.
<b>Ultra tri-band (UTB) filtering</b>	No	No	No

	HPE Aruba Networking AP-763 (JPF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Indoor AP (S4K16A)	HPE Aruba Networking AP-763 (RW) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Indoor AP (S4K10A)	HPE Aruba Networking AP-763 (RWF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Indoor AP (S4K15A)
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-763 (US) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Indoor AP (S4K09A)	HPE Aruba Networking AP-763 (USF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Indoor AP (S4K14A)	HPE Aruba Networking AP-764 (EG) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened AP (S4K38A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	External antenna support: Two sets of two (female) RP-SMA connectors for external antennas (DB0 and DB1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, 6G0 and 6G1 corresponding with radio chains 0 and 1 for the 6 GHz radio). - Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.
<b>Ultra tri-band (UTB) filtering</b>	No	No	No

	HPE Aruba Networking AP-763 (US) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Indoor AP (S4K09A)	HPE Aruba Networking AP-763 (USF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Indoor AP (S4K14A)	HPE Aruba Networking AP-764 (EG) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened AP (S4K38A)
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited Lifetime Warranty (LLW)
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-764 (EGF1) Flex Radio 2x2 Wi-Fi 7 Connectorized TAA Hardened AP (S4K43A)	HPE Aruba Networking AP-764 (ID) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened Access Point (S6A20A)	HPE Aruba Networking AP-764 (IL) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened AP (S4K37A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	External antenna support: Two sets of two (female) RP-SMA connectors for external antennas (DB0 and DB1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, 6G0 and 6G1 corresponding with radio chains 0 and 1 for the 6 GHz radio). - Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.	External antenna support: Two sets of two (female) RP-SMA connectors for external antennas (DB0 and DB1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, 6G0 and 6G1 corresponding with radio chains 0 and 1 for the 6 GHz radio). - Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.	External antenna support: Two sets of two (female) RP-SMA connectors for external antennas (DB0 and DB1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, 6G0 and 6G1 corresponding with radio chains 0 and 1 for the 6 GHz radio). - Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.
<b>Ultra tri-band (UTB) filtering</b>	No	No	No
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10

	HPE Aruba Networking AP-764 (EGF1) Flex Radio 2x2 Wi-Fi 7 Connectorized TAA Hardened AP (S4K43A)	HPE Aruba Networking AP-764 (ID) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened Access Point (S6A20A)	HPE Aruba Networking AP-764 (IL) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened AP (S4K37A)
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-764 (ILF1) Flex Radio 2x2 Wi-Fi 7 Connectorized TAA Hardened AP (S4K42A)	HPE Aruba Networking AP-764 (JP) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened AP (S4K36A)	HPE Aruba Networking AP-764 (JPF1) Flex Radio 2x2 Wi-Fi 7 Connectorized TAA Hardened AP (S4K41A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	External antenna support: Two sets of two (female) RP-SMA connectors for external antennas (DB0 and DB1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, 6G0 and 6G1 corresponding with radio chains 0 and 1 for the 6 GHz radio). - Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.	External antenna support: Two sets of two (female) RP-SMA connectors for external antennas (DB0 and DB1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, 6G0 and 6G1 corresponding with radio chains 0 and 1 for the 6 GHz radio). - Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.	External antenna support: Two sets of two (female) RP-SMA connectors for external antennas (DB0 and DB1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, 6G0 and 6G1 corresponding with radio chains 0 and 1 for the 6 GHz radio). - Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.
<b>Ultra tri-band (UTB) filtering</b>	No	No	No
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10

	HPE Aruba Networking AP-764 (ILF1) Flex Radio 2x2 Wi-Fi 7 Connectorized TAA Hardened AP (S4K42A)	HPE Aruba Networking AP-764 (JP) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened AP (S4K36A)	HPE Aruba Networking AP-764 (JPF1) Flex Radio 2x2 Wi-Fi 7 Connectorized TAA Hardened AP (S4K41A)
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-764 (RW) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened AP (S4K35A)	HPE Aruba Networking AP-764 (RWF1) Flex Radio 2x2 Wi-Fi 7 Connectorized TAA Hardened AP (S4K40A)	HPE Aruba Networking AP-764 (US) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened AP (S4K34A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	External antenna support: Two sets of two (female) RP-SMA connectors for external antennas (DB0 and DB1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, 6G0 and 6G1 corresponding with radio chains 0 and 1 for the 6 GHz radio). - Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.	External antenna support: Two sets of two (female) RP-SMA connectors for external antennas (DB0 and DB1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, 6G0 and 6G1 corresponding with radio chains 0 and 1 for the 6 GHz radio). - Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.	External antenna support: Two sets of two (female) RP-SMA connectors for external antennas (DB0 and DB1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, 6G0 and 6G1 corresponding with radio chains 0 and 1 for the 6 GHz radio). - Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.
<b>Ultra tri-band (UTB) filtering</b>	No	No	No
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)

	HPE Aruba Networking AP-764 (RW) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened AP (S4K35A)	HPE Aruba Networking AP-764 (RWF1) Flex Radio 2x2 Wi-Fi 7 Connectorized TAA Hardened AP (S4K40A)	HPE Aruba Networking AP-764 (US) Flex Radio 2x2 Wi-Fi 7 Connectorized Hardened AP (S4K34A)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-764 (USF1) Flex Radio 2x2 Wi-Fi 7 Connectorized TAA Hardened AP (S4K39A)	HPE Aruba Networking AP-765 (EG) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Outdoor AP (S4K23A)	HPE Aruba Networking AP-765 (EGF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Outdoor AP (S4K28A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	External antenna support: Two sets of two (female) RP-SMA connectors for external antennas (DB0 and DB1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, 6G0 and 6G1 corresponding with radio chains 0 and 1 for the 6 GHz radio). - Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.
<b>Ultra tri-band (UTB) filtering</b>	No	No	No

	HPE Aruba Networking AP-764 (USF1) Flex Radio 2x2 Wi-Fi 7 Connectorized TAA Hardened AP (S4K39A)	HPE Aruba Networking AP-765 (EG) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Outdoor AP (S4K23A)	HPE Aruba Networking AP-765 (EGF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Outdoor AP (S4K28A)
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited Lifetime Warranty (LLW)	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-765 (ID) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Outdoor AP (S6A21A)	HPE Aruba Networking AP-765 (IL) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Outdoor AP (S4K22A)	HPE Aruba Networking AP-765 (ILF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Outdoor AP (S4K27A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.
<b>Ultra tri-band (UTB) filtering</b>	No	No	No

	HPE Aruba Networking AP-765 (ID) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Outdoor AP (S6A21A)	HPE Aruba Networking AP-765 (IL) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Outdoor AP (S4K22A)	HPE Aruba Networking AP-765 (ILF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Outdoor AP (S4K27A)
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-765 (JP) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Outdoor AP (S4K21A)	HPE Aruba Networking AP-765 (JPF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Outdoor AP (S4K26A)	HPE Aruba Networking AP-765 (RW) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Outdoor AP (S4K20A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.
<b>Ultra tri-band (UTB) filtering</b>	No	No	No

	HPE Aruba Networking AP-765 (JP) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Outdoor AP (S4K21A)	HPE Aruba Networking AP-765 (JPF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Outdoor AP (S4K26A)	HPE Aruba Networking AP-765 (RW) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Outdoor AP (S4K20A)
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-765 (RWF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Outdoor AP (S4K25A)	HPE Aruba Networking AP-765 (US) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional Outdoor AP (S4K19A)	HPE Aruba Networking AP-765 (USF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Outdoor AP (S4K24A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz (4x4) with 160 MHz (AP-763 and AP-765 models only) 5 GHz (4x4) with 80 MHz (AP-763 and AP-765 models only) 6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.	Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional). - Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4). - Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees. - Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4). - Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.
<b>Ultra tri-band (UTB) filtering</b>	No	No	No

	HPE Aruba Networking AP-765 (RWF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Outdoor AP (S4K25A)	HPE Aruba Networking AP-765 (US) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Outdoor AP (S4K19A)	HPE Aruba Networking AP-765 (USF1) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional TAA Outdoor AP (S4K24A)
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)	WiFi Alliance®: WiFi CERTIFIED® a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi-Fi agile multiband Bluetooth SIG Ethernet Alliance (EO, PoE PD Device Class 6)
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-765EX (EG) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S4K33A)	HPE Aruba Networking AP-765EX (ID) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S6A22A)	HPE Aruba Networking AP-765EX (IL) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S4K32A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	<p>Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional).</p> <ul style="list-style-type: none"> <li>- Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4).</li> <li>- Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees.</li> <li>- Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4).</li> <li>- Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.</li> </ul>	<p>Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional).</p> <ul style="list-style-type: none"> <li>- Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4).</li> <li>- Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees.</li> <li>- Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4).</li> <li>- Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.</li> </ul>	<p>Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional).</p> <ul style="list-style-type: none"> <li>- Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4).</li> <li>- Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees.</li> <li>- Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4).</li> <li>- Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.</li> </ul>
<b>Ultra tri-band (UTB) filtering</b>	No	No	No
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor

	HPE Aruba Networking AP-765EX (EG) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S4K33A)	HPE Aruba Networking AP-765EX (ID) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S6A22A)	HPE Aruba Networking AP-765EX (IL) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S4K32A)
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance: WiFi certified a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi Fi agile multiband Bluetooth SIG • Ethernet Alliance (EO, PoE PD Device Class 6) Class 1 Division 2/Class 2 Division 2 ATEX Zone 2 IECEX	WiFi Alliance: WiFi certified a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi Fi agile multiband Bluetooth SIG • Ethernet Alliance (EO, PoE PD Device Class 6) Class 1 Division 2/Class 2 Division 2 ATEX Zone 2 IECEX	WiFi Alliance: WiFi certified a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi Fi agile multiband Bluetooth SIG • Ethernet Alliance (EO, PoE PD Device Class 6) Class 1 Division 2/Class 2 Division 2 ATEX Zone 2 IECEX
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

	HPE Aruba Networking AP-765EX (JP) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S4K31A)	HPE Aruba Networking AP-765EX (RW) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S4K30A)	HPE Aruba Networking AP-765EX (US) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S4K29A)
<b>Deployment</b>	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor	Hardened; Outdoor; Industrial; Ruggedized; Indoor
<b>Wi-Fi generation</b>	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)	Wi-Fi 7 (802.11be)
<b>Wi-Fi radios</b>	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz	Dual 2x2 MIMO radios, triband coverage (2.4 GHz, 5 GHz, 6 GHz) or single 4x4 MIMO radio in 5 GHz or 6 GHz
<b>Radio configuration options</b>	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz	6 GHz + 5 GHz (2x2) with 160/80 MHz 6 GHz + 2.4 GHz (2x2) with 80/40 MHz 5 GHz + 2.4 GHz (2x2) with 80/40 MHz
<b>Max bandwidths and peak data rate per band</b>	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz	20/40/80/160 MHz channel bandwidths supported Aggregate peak data rate 5.8 Gbps using 6 GHz (4x4) with 160 MHz
<b>Wi-Fi antenna</b>	<p>Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional).</p> <ul style="list-style-type: none"> <li>- Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4).</li> <li>- Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees.</li> <li>- Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4).</li> <li>- Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.</li> </ul>	<p>Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional).</p> <ul style="list-style-type: none"> <li>- Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4).</li> <li>- Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees.</li> <li>- Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4).</li> <li>- Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.</li> </ul>	<p>Integrated tri-band dynamic antennas (software-provisionable omnidirectional or directional).</p> <ul style="list-style-type: none"> <li>- Omnidirectional Mode - peak antenna gain of 2.8 dBi in 2.4 GHz (2x2), 3.9 dBi in 5 GHz (2x2), 3.0 dBi in 5 GHz (4x4), 3.3 dBi in 6 GHz (2x2), and 3.2 dBi in 6 GHz (4x4).</li> <li>- Omnidirectional mode antennas are optimized for horizontal ceiling mounted orientation of the access points. The down-tilt angle for maximum gain is roughly 10 to 20 degrees.</li> <li>- Directional Mode - peak antenna gain of 6.1 dBi in 2.4 GHz (2x2), 6.0 dBi in 5 GHz (2x2), 6.1 dBi in 5 GHz (4x4), 7.4 dBi in 6 GHz (2x2), and 7.2 dBi in 6 GHz (4x4).</li> <li>- Directional mode antennas are optimized for wall or pole mounting for directional coverage with the orientation of the access points facing the direction of coverage with approximately 90° x 90° beamwidth.</li> </ul>
<b>Ultra tri-band (UTB) filtering</b>	No	No	No
<b>IoT support</b>	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB	BLE 5.4 w/HADM 802.15.4/Zigbee USB
<b>Integrated sensor</b>	Barometric sensor	Barometric sensor	Barometric sensor

	HPE Aruba Networking AP-765EX (JP) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S4K31A)	HPE Aruba Networking AP-765EX (RW) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S4K30A)	HPE Aruba Networking AP-765EX (US) Flex Radio 2x2 Wi-Fi 7 Dynamic Omni-Directional HazLoc AP (S4K29A)
<b>Location services</b>	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver	802.11 FTM support; Built-in GPS; GNSS receiver
<b>Cellular support</b>	No	No	No
<b>Wired network interface</b>	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)	1 x 5GbE (auto-sensing link speed 100/1000/2500/5000BASE-T and MDI/MDIX)
<b>MACsec support</b>	Yes	Yes	Yes
<b>AP operating system support</b>	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10	HPE Aruba Networking Wireless Operating System 10
<b>AP management</b>	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises	Public Cloud; Virtual Private Cloud (VPC); as a Service; On-premises
<b>Certifications</b>	WiFi Alliance: WiFi certified a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi Fi agile multiband Bluetooth SIG • Ethernet Alliance (EO, PoE PD Device Class 6) Class 1 Division 2/Class 2 Division 2 ATEX Zone 2 IECEX	WiFi Alliance: WiFi certified a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi Fi agile multiband Bluetooth SIG • Ethernet Alliance (EO, PoE PD Device Class 6) Class 1 Division 2/Class 2 Division 2 ATEX Zone 2 IECEX	WiFi Alliance: WiFi certified a, b, g, n, ac, 6, 7 WPA2 and WPA3 (enterprise, personal), Enhanced Open (OWE) WMM, WMM PS, Wi Fi agile multiband Bluetooth SIG • Ethernet Alliance (EO, PoE PD Device Class 6) Class 1 Division 2/Class 2 Division 2 ATEX Zone 2 IECEX
<b>Regulatory</b>	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112	FCC/ISED CE marked EU RED with NB TA (as needed) ETSI EN 300328 2.4GHz ETSI EN 301893 5GHz ETSI EN 303687 (6GHz) EN301489-1 / 489-17 EN 300440 EN 303413 GNSS (GPS) IEC/EN 623681 EN 6060111, EN6060112
<b>Warranty</b>	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.	Limited lifetime warranty. See the warranty duration.
<b>Ports</b>	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console	1 x 5GbE USB 2.0 Reset button Serial console

# HPE Aruba Networking Services

HPE Aruba Networking services simplify and accelerate the network technology lifecycle, enabling your network to scale with better predictability and cost-effectiveness. Whether you operate your own network and need to improve your IT efficiencies, or you want to offload some of the burden, we have the services you need to reach your goals.

Learn more about what HPE Services - Aruba Networking has to offer at: [hpe.com/edge/services](https://hpe.com/edge/services)

## Support Services

Our support portfolio provides the essential support elements as well as proactive and preventive features to help you improve your team's productivity and get the most from your network. Our support customers benefit from faster issue resolution, simplified operations and efficiencies, and reduced network issues.

## Professional Services

With deep intellectual capital and purpose-built tools, our team delivers a range of standard and custom professional services designed to accelerate your value from HPE Aruba Networking technology.

### Project based services include:

- Planning, audit, and assessment
- Architecture review and design
- Deployment, migration, and knowledge transfer

### Annual subscription services include:

- Network optimization
- Intelligent Operations
- Customer Experience Management

Our [Education Services](#) allow your team to come up to speed quickly.

## GreenLake for Networking

Deliver innovative business outcomes by leveraging new ways to consume, deploy and [manage networks](#).

[For additional technical information, available models and options, please reference the QuickSpecs](#)

Visit [HPE.com](https://www.hpe.com)

[Chat now](#)

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Bluetooth is a trademark owned by its proprietor and used by Hewlett Packard Enterprise under license. Wi-Fi and Wi-Fi Alliance are registered trademarks of Wi-Fi Alliance. All third-party marks are property of their respective owners.

Image may differ from the actual product.

[PSN1014901369NOEN](#), May, 2026.

HEWLETT PACKARD ENTERPRISE

[hpe.com](https://www.hpe.com)

