

# HPE Networking Comware Switch Series 5945



---

## What's new

- High-density 100GbE/40GbE/25GbE/10GbE spine/top-of-rack (ToR) connectivity and Cut-through switching with low-latency and wire speed performance.
- New 32G/16G FC support for storage networking and ROCE V1/V2 for RDMA High-Performance computing.
- Greater flexibility with two/four slot options for varying use cases such as MACsec encryption, high-performance DC leaf, storage networking with FC and NVMe storage.

## Overview

The HPE FlexFabric 5945 Switch Series are high-density, ultra-low-latency, and top-of-rack (ToR) switches ideally suited for deployment at the aggregation or server access layer of large enterprise data centers. The HPE 5945 is also powerful enough for deployment at the core layer of medium-sized enterprises. With the increase in virtualized applications and server-to-server traffic, customers require spine and ToR switches that can meet their throughput requirements. With the HPE 5945, data centers can now support up to 100GbE per port, allowing high performance server connectivity and the capabilities to handle virtual environments. The HPE FlexFabric 5945 Switch Series provides choices that fit your budget and IT environment by cut-through with ultra-low-latency and wire speed, offering different port density and

- VXLAN, EVPN, and MPLS support for virtualized environments.
- IPv4 and IPv6 support with full L2/L3 features and PTP 1588V2 for Boundary Clock, Transparent Clock, End to End/Peer to Peer Transparent Clock.
- HPE IMC Orchestrator and Analyzer for enhanced network operations with orchestration, automation, and analytical capabilities.

speeds of 100GbE/40GbE/25GbE/10GbE spine/ToR connectivity.

## Features

### High-density, Advanced, Data Center Switches with HPE FlexFabric Network Analytics

The HPE FlexFabric 5945 Switch Series enables customers to scale their server-edge 1/10/25/40/100GbE top-of-rack (ToR) deployments with high-density 48 x 10GbE (SFP or BASE-T) with 6 x 40GbE ports, 48 x 10GbE (SFP or BASE-T) with 6 x 100GbE ports, 32 x 40GbE ports, and 32 x 100 GbE ports.

Available with a 2-slot modular version delivering two 40GbE or 100GbE ports, 48 x 10/25GbE, 4 x 100GbE, or up to 16 x 100GbE from modules.

A 4-slot modular version is also available with four 40GbE ports.

HPE IMC Orchestrator and Analyzer offers enhanced network operations with orchestration, automation, and analytical capabilities.

### High-performance Data Center Switching

The HPE FlexFabric 5945 Switch Series delivers up to 2.56 Tbps switching capacity for demanding data center applications.

Supports up to 1904 MPPS throughput for data-intensive environments.

Low latency, under 1s for 40GbE, delivering increased network throughput.

VXLAN support for network virtualization and overlay solutions for improved flexibility. Includes Open vSwitch Database (OVSDDB) for dynamic VXLAN tunnel management.

### Business Agility and Resilience with Hewlett Packard Enterprise Comware 7

The HPE FlexFabric 5945 Switch Series delivers Hewlett Packard Enterprise Intelligent Resilient Fabric (IRF) with <50 msec convergence time enabling faster application response time.

The In-Service Software Update (ISSU) enables high availability with modular updates accomplished without a reboot or power cycle, in the background.

### Simplicity and Lower TCO

HPE FlexFabric 5945 Switch Series simplifies switch management by up to 88% with 9-unit Hewlett Packard Enterprise Intelligent Resilient Fabric (IRF).

No hidden costs with simple one license per switch for all operating system features.

All switch ports are active and ready to use without the need for activation licenses.



**Technical specifications****HPE Networking Comware Switch Series 5945**






<b>Ports</b>	48 x 25 Gb SFP28, 8 x 100 Gb QSFP28 and 2 x 1 Gb SFP ports or 2 module slots and 2 x 100 Gb QSFP28 ports, supporting up to a maximum of 48 x 10/25GbE and 4 x 100GbE ports, or up to 16 x 100GbE ports from modules; or 4 module slots and 2 x 1 Gb SFP ports, supporting up to a maximum of 96 x 10/25GbE and 8 x 100GbE ports, or up to 32 x 100GbE ports; 32 x 100 Gb QSFP28 ports; 2 x 1 Gb SFP ports depending on model
<b>Memory and processor</b>	1 GB flash Packet buffer size: 16 MB, 4 GB SDRAM
<b>Latency</b>	< 1 $\mu$ s (64-byte packets)
<b>Throughput</b>	up to 2024 Mpps
<b>Routing/switching capacity</b>	6.4 Tbps, maximum, depending on model and configuration
<b>Stacking capabilities</b>	up to 10 HPE 5945 switches
<b>Management features</b>	IMC, CLI, out-of-band management, SNMP Manager, Telnet, FTP
<b>Input voltage</b>	100 VAC to 240 VAC, or -40 VDC to -60 VDC, depending on installed power supplies
<b>Power consumption</b>	650W maximum



For additional technical information, available models and options, please reference the [QuickSpecs](#)

**Make the right purchase decision.  
Contact our presales specialists.**

[Find a partner](#)



© Copyright 2024 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Image may differ from the actual product  
[PSN1010907030HKEN](#), May, 2024.