



# HPE SUPERDOME FLEX 280 SERVER

## Superdome Flex Servers



### WHAT'S NEW

- Additional processor and I/O choices.
- Support for Intel® Optane™ Persistent Memory 200 series for HPE.
- NVMe drives/tri-mode controller support.
- Support for 6-socket configuration.

### OVERVIEW

Are you looking to equip your enterprise environment with the performance, reliability, and security needed for the most demanding workloads?

The HPE Superdome Flex 280 is a highly reliable server that starts at two and scales up to eight 3rd generation Intel® Xeon® Scalable processors. Its modular architecture scales cost-efficiently to meet future growth. Six UPI links per processor result in higher bandwidth and faster data rates than prior generations. [1] Designed to provide 64 GB to 24 TB of shared memory using DRAM or in combination with persistent memory, it is an ideal choice for real-time analytics. Extreme HPE Superdome RAS features such as advanced memory resiliency, firmware-first approach, analysis engine, and self-healing provide increased system uptime. Superior security, including support for Silicon Root of Trust, protects your critical workloads. As-a-service consumption with HPE GreenLake provides flexibility while maintaining on-premises control.

## FEATURES

### Meet Evolving Business Demands with Optimum Flexibility

HPE Superdome Flex 280 server utilizes a modular 5U 2- or 4-socket building block. It scales cost-efficiently from two to eight sockets to meet future growth.

Leverage a choice of either economical Gold or high-end Platinum 3rd generation Intel Xeon Scalable processors to deliver 16 to 224 powerful compute cores in a single system.

As-a-service option with HPE GreenLake provides consumption flexibility while maintaining on-premises control.

Simplify management with a comprehensive framework that includes HPE OneView management, OpenStack, Redfish APIs, and an easy-to-use management GUI.

### Address the Most Demanding Workloads with Increased Performance

HPE Superdome Flex 280 server modular architecture features six UPI links per processor and delivers higher bandwidth and faster data rates than prior generations. [1]

Designed to provide 64 GB to 24 TB of shared memory using DRAM only or in combination with Intel Optane Persistent Memory 200 Series for HPE, HPE Superdome Flex 280 server is ideal for in-memory analytics.

Address large data volumes and network connectivity with a balanced I/O system supporting up to 32 PCIe 3.0 cards with choice of 16-slot (all low profile) or 12-slot (FH/FW). The server supports up to 20 SAS/SATA/NVMe drives with RAID and hardware encryption, plus an optional DVD.

### Safeguard Critical Workloads with Extreme Reliability and Superior Security

The HPE Superdome Flex 280 server features a comprehensive set of RAS capabilities to deliver the highest service levels for mission critical applications.

Contain errors at the firmware level, including memory errors, before any interruption can occur at the operating system layer with the HPE firmware-first approach.

Reduce human error with the proven fault-handling analysis engine, which predicts hardware faults and initiates self-repair without operator assistance.

Reduce exposure to threats and protects against firmware attacks and malware with superior security capabilities, including Silicon Root of Trust.

Deliver business continuity for Linux® workloads with HPE Serviceguard for Linux (SGLX) high-availability and disaster recovery clustering solution. It protects from a multitude of infrastructure and application faults across physical or virtual environments over any distance.



## Technical specifications

## HPE Superdome Flex 280 Server

<b>Processor Type</b>	Intel®
<b>Processor Name</b>	Intel Xeon Scalable processors (Platinum or Gold)
<b>Processor family</b>	Four Intel® Xeon® Scalable processors (Platinum or Gold) per chassis
<b>Processor core available</b>	28 or 24 or 20 or 18 or 16 or 8
<b>Processor cache</b>	16.5 MB or 22 MB or 24.75 MB or 27.5 MB or 33 MB or 35.75 MB or 38.5 MB
<b>Processor speed</b>	3.9 GHz maximum depending on processor
<b>Drive type</b>	Up to twenty 2.5-inch SFF SAS/SATA SSDs or SATA HDDs. 10 per chassis
<b>Drive description</b>	0 to 20
<b>Network controller</b>	2 x 1GbE ports per base chassis onboard. Additional networking available via I/O cards.
<b>Maximum memory</b>	Designed for up to 24 TB of memory in an 8-socket system
<b>Memory type</b>	DDR4 Memory with Optional Persistent Memory
<b>Memory slots</b>	48 DIMM slots per chassis
<b>Expansion slots</b>	Up to 16 per chassis, for detail descriptions refer to the QuickSpecs. Options include 12-slot with full height capability 16-slot zero slots - compute only
<b>Power supply type</b>	HPE 1600W hot-swappable. Optional 2130W hot swappable. Up to 4 per chassis
<b>Infrastructure management</b>	Web-based GUI, command-line, and Redfish
<b>System fan features</b>	Hot-plug
<b>Form factor</b>	Chassis is a 5U enclosure
<b>Optical drive type</b>	DVD-RW or DVD-R
<b>Product Dimensions (metric)</b>	21.82 x 44.45 x 87.95 cm (chassis), not including mounting rails for width, measured handle to handle for depth
<b>Weight</b>	Average 50 kg
<b>Warranty</b>	3-year parts, 3-year labor, 3-year onsite support coverage. For more warranty information refer to <a href="https://h20564.www2.hp.com/hpsc/wc/public/home">https://h20564.www2.hp.com/hpsc/wc/public/home</a> . Additional HPE support and service coverage for your product can be purchased locally. For information on availability of service upgrades and the cost for these service upgrades, refer to the HPE website at <a href="http://hpe.com/support">http://hpe.com/support</a> .



For additional technical information, available models and options, please reference the [QuickSpecs](#)

## HPE POINTNEXT SERVICES

[HPE Pointnext Services](#) brings together technology and expertise to help you drive your business forward and prepare for whatever is next.

### Operational Services from HPE Pointnext Services

[HPE Pointnext Tech Care](#) provides fast access to product-specific experts, an AI-driven digital experience, and general technical guidance to help enable constant innovation. We have reimagined IT support from the ground up to deliver faster answers and greater value. By continuously searching for better ways to do things—as opposed to just fixing things that break—HPE Pointnext Tech Care helps you focus on achieving your business goals.

[HPE Pointnext Complete Care](#) is a modular, edge-to-cloud IT environment service that provides a holistic approach to optimizing your entire IT environment, and achieving agreed upon IT outcomes and business goals through a personalized and customer-centric experience. All delivered by an assigned team of HPE Pointnext Services experts.

**HPE Integration and Performance Services** help you customize your experience at any stage of your product lifecycle with a menu of services based on individual needs, workloads, and technologies.

- Advise, design, and transform
- Deploy
- Integrate and migrate
- Operate and improve
- Financial Services
- Greenlake Management Services
- Retire and sanitize
- IT Training and personal development

### Other related services

[HPE Education Services](#) delivers a comprehensive range of services to support your people as they expand their skills required for a digital transformation. Consult your HPE Sales Representative or Authorized Channel Partner of choice for any additional questions and support options.

**Defective Media Retention** is optional and allows you to retain Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

## HPE GREENLAKE

[HPE Greenlake](#) is HPE's market-leading IT as-a-Service offering that brings the cloud experience to apps and data everywhere – data centers, multi-clouds, and edges – with one unified operating model. HPE GreenLake delivers public cloud services and infrastructure for workloads on premises, fully managed in a pay per use model.

If you are looking for more services, like **IT financing solutions**, please [explore them here](#).

[1] The 3rd-generation Intel Xeon Scalable processor architecture has six UPI links, twice than the 2nd generation Intel Xeon Scalable processor architecture. Maximum data rate is 3200 MT/s @ 1 DPC, 9% higher than with 2nd generation Intel Xeon Scalable processors.

Make the right purchase decision.  
Contact our presales specialists.

[Call for availability](#)



Chat now (sales)



Call now



Share now



Get updates

**Hewlett Packard  
Enterprise**

© Copyright 2022 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Intel Xeon and Intel Optane are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. SAP HANA is a trademark or registered trademark of SAP SE (or an SAP affiliate company) in Germany and other countries. Oracle is a registered trademark of Oracle and/or its affiliates. All third-party marks are property of their respective owners.

Image may differ from the actual product  
[PSN1012865453EMEA\\_AFRICAEN](#), August, 2022.